Preliminary Engineers Report Judicial Ditch No. 414 Branch A40 Martin County and Faribault County, Minnesota

Date: February 7, 2020

ISG Project No.: 19-23608



Architecture Engineering Environmental Planning ISGInc.com REPORT FOR: Martin – Faribault Joint Drainage Authority Drainage System Manager 201 Lake Avenue + Suite #201 Fairmont, Minnesota 56081 507.238.3130 michael.forstner@co.martin.mn.us FROM: ISG Mark Origer, **PE** Civil Engineer 115 E Hickory Street + Suite #300 Mankato, Minnesota 56001 507.387.6651 Mark.Origer@ISGInc,com I hereby certify that this plan, specification, or report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the state of Minnesota.

Mark Vriger Signature:

Printed Name: Mark Origer, PE

License Number: 54863

ISG 115 E Hickory Street, Suite 300 Mankato, Minnesota 56001

Judicial Ditch No. 414 Branch A40 Improvements

Martin County and Faribault County, Minnesota

Engineer's Project Number: 19-23608

Dated this 7th day of February, 2020

TABLE OF CONTENTS

| Petition + Order | 1 |
|---|---|
| Petition Summary | 1 |
| Order Summary | 1 |
| System Watershed | 1 |
| Location | 1 |
| Watershed Description | 2 |
| History | 2 |
| Early Coordination | 2 |
| Investigation of External Sources of Funding and Technical Assistance | 2 |
| Present Condition | 3 |
| System Capacity | 3 |
| Nature and Capacity of the Outlet | 3 |
| Statute Required + Suggested Efforts | 4 |
| Project Necessity | 4 |
| Environmental, Land Use, and Multipurpose Water Management Considerations | 4 |
| (Section 103E.015, Subd. 1) | 4 |
| Statement of Necessity and Feasibility, Section 103E.015, Subd. 1, | 6 |
| Substantial Affect on Public Waters | 6 |
| Proposed Project | 6 |
| Project Design Parameters | 7 |
| Coefficient of Drainage | 7 |
| System Depth | 7 |
| Erosion Control | 7 |
| Tile and Connection Materials | 7 |
| Tile Replacement and Connections | 7 |
| Project Components | 7 |
| Tile | 7 |
| Drop Inlet | 8 |
| Storage | 9 |
| Preliminary Cost Estimates | 9 |
| Separable Maintenance | 9 |
| Summary of Findings, Conclusions + Recommendations | |
| Preliminary Plans | |

APPENDICES

| Appendix A: Preliminary Plans | A |
|---|-----|
| Appendix B: Order + Petition | . В |
| Appendix C: Maps | C |
| Appendix D: Multipurpose Drainage Management Plan | . D |
| Appendix E: Modeling with Maps | E |
| Appendix F: Preliminary Cost Estimate | F |

EXECUTIVE SUMMARY

A petition was submitted to the Martin – Faribault County Joint Drainage Authority requesting an improvement to a portion of the Judicial Ditch No. 414 (JD 414) public drainage system. The petitioners requested to improve Branch A40 and its associated branches, which include Branch A43, A45, A46, and A47. Judicial Ditch No. 414 has a watershed of 10,893 acres consisting of gently rolling agricultural land and Branch A40 and its branches has a watershed of 453 acres. The system was constructed in 1910 with major repair completed in 2018, which included cleaning entire mainline open ditch and addressing maintenance items.

ISG prepared a feasibility report for landowners within the drainage system which then progressed into meeting with all landowners within the drainage system and county staff. Concluding the meetings, there was a general concern with the system's ability to drain portions of the watershed due to tile capacity issues along with failing tiles issues.

Currently, Branch A40 tile outlets into JD 414 open ditch with a 14-inch tile and has a drainage coefficient of 0.13 inches per day. Throughout the remaining portions of Branch A40 and its branches, drainage coefficients are consistently under the recommended drainage capacities.

The proposed projects include upsizing and deepening Branch A40 and its branches. The project includes installing approximately 6,700 linear feet of tile ranging from 24- to 8-inch tile generally following the existing tile alignments. The proposed tiles are improved to achieve the recommended 0.50 in/day drainage coefficient. A 1-acre storage pond located at the outlet of Branch A40 is recommended to be included with the improvement project. This location was determined to be the most cost effective, although other options may be explored upon landowner or county input. The proposed project as outlined above is referenced as at Option 2 within this report. Two alternative storage options are included which implement no storage and a 3-acre pond located at the outlet of Branch A40 as Option 1 and Option 3, respectively.

The preliminary estimated construction cost for JD 414 improvement Option 2 to improve drain tiles is approximately \$483,200. The storage basin construction cost for Option 2 is approximately \$92,100 to purchase permanent flowage easement for property, excavating the pond, control structures, and grade out the pond spoils. The total preliminary estimated construction for Option 2 is \$605,000.

PETITION + ORDER

Petition Summary

A Petition was received by the Martin – Faribault Joint Drainage Authority on August 2, 2019 to improve a portion of Judicial Ditch No. 414. The petitioners requested that the Drainage Authority improve Branch A40 and its branches, which include tile branches A40, A43, A45, A46, and A47. A copy of the signed Petition has been placed in Appendix B.

Order Summary

On September 17th, 2019 the Martin – Faribault Joint Drainage Authority, in regular session, made an Order related to the Petition in which it appointed ISG as the engineer. A copy of the signed Order has been placed in Appendix B.

SYSTEM WATERSHED

Location

Judicial Ditch No. 414 Branch A40 is located in Sections 3, 4, 7-10, 15-20, 29, and 30 of Pilot Grove Township in Faribault County and Sections 13-29 of East Chain Township in Martin County. The mainline open ditch runs generally northeast from its end in Section 17 of East Chain Township in Martin County to Section 3 of Pilot Grove Township in Faribault County to its outlet, County Ditch No. 514.

Branch A40 is located in Section 19 and 30 of Pilot Grove Township in Faribault County and Section 25 of East Chain Township in Martin County. Branch A40 flows generally northwest to its outlet into the mainline open ditch. Branch A40 contains 5 braches: Branch A41, Branch A43, Branch A45, Branch A46, and Branch A47.

Martin – Faribault County Judicial Ditch No. 414 Branch A40 Preliminary Engineers Report Watershed Description

Judicial Ditch No. 414 drains 10,893 acres and servers as an outlet to Judicial Ditch 314 draining 3,443 acres. Its watershed is characterized as relatively flat with an elevation difference of approximately 45-feet. Branch A40 and its branches drain 453 acres.

The predominant hydrologic soil type in the system's watershed is type "C/D" according to the Web Soil Survey (WSS). This classification "C" represents the drained condition with type "D" represents the undrained condition. The soils consist of silty clay loam soils that, when adequately drained, are prime for farmland. A level 1 wetland delineation was completed, and Branch A40 has potential wetlands located along County Road 2.

See Appendix C for maps depicting the watershed's location, elevation, hydrologic soils, unified soil classification, and Level 1 Wetland Delineation.

HISTORY

According to material supplied by Martin County and Faribault County, Judicial Ditch 414 was first constructed as part of Judicial Ditch No. 14 in 1910. During a re-determination of benefits in 2012-2013, the Judicial Ditch No. 14 system was divided into the current systems which include Judicial Ditch No. 214, Judicial Ditch No. 314, Judicial Ditch, 414, and County Ditch No. 514. The JD 414 system currently consisting of 92,015-feet of open ditch including the mainline and branches and 210,370-feet of tile including the mainline and branches.

Maintenance records indicate that JD 414 underwent repairs in 1950 consisting of open ditch cleaning. In the mid 1970's improvements were completed on the mainline open ditch, Branch A1, A2, A6, A7, and A20. A major repair was completed in 2018, which included cleaning the entire mainline open ditch and addressing maintenance items such as slough repairs, tile outlet repairs, buffer seeding, and alternative side inlet installation.

No known repairs or improvements have been completed on Branch A40, A43, A45, A6 or A47.

Early Coordination

Prior to the Petition for this drainage project a landowner meeting was held which were attended by the Engineer, county drainage staff, ISG staff, and watershed landowners. In response, the Engineer prepared a Feasibility Report which included options for repair and improvement of Branch A40 and is branches. The feasibility report formed the bases for both the petition and present report.

Investigation of External Sources of Funding and Technical Assistance

Section 103E.015, Subd. 1a of the Drainage Code requires that an investigation of external sources of funding and technical assistance be conducted prior to the appointment of an engineer for a drainage project or a petitioned repair. The funding can be used for wetland preservation or restoration or creation of water quality improvements, flood control, or alternative measures (per Section 103E.015, Subd. 1, clause (2)). The sources of funding authorized under this Section can be used outside the benefited area, but must be used in the watershed of the system.

A multipurpose drainage management (MDM) map is included in Appendix D. The MDM map shows potential locations for additional best management practices (BMPs) and will be proposed to landowners.

Due to limited BMPs that can be implemented in coordination with tile installation, additional BMPs may be implemented independently by individual landowners. These practices include nutrient management, conservation tillage, cover crops, blind rock inlets, and controlled drainage. The respective counties Soil and Water Conservation District (SWCD) representative can assist landowners with implementation and available funding.

Through the improvement project, it is recommended to implement a 1-acre storage pond. The storage pond will provides waterholding capacity within the watershed to reduces peak flow rates discharges from the system as well as providing ability for sedimentation and denitrification. Although there are many grants available in the state of Minnesota that support water quality, for many of the grants storage ponds are not considered an eligible practice. The investigation of sources of external funds will continue as the project moves forward and will include BWSR MDM grants, the Greater Blue Earth River Basin Alliance, and other MDM grants.

System Capacity

The following tables summarize the hydraulic analysis of Branch 40A and its branches in the As Constructed or Subsequently Improved Condition (ACSIC). The capacities listed in the tables reference the capacity of agricultural drainage which is expressed as a drainage coefficient (CD) and is defined as the depth of water over the entire area of the upstream watershed that a tile or ditch can drain in a 24-hour period (inches per day (in/day)). For a system like JD 414 Branch A40, drainage coefficients of 0.375 in/day to 0.50 in/day for tile are recommended for today's drainage needs.

| Branch | ACSIC Size (in) | ACSIC Slope (%) | Drainage Area (Acres) | ACSIC Drainage Coefficient (in/day) |
|--------|--------------------|--------------------|--------------------------|--|
| A40 | 14 | 0.20% | 427.4 | 0.13 |
| A40 | 12 | 0.20% | 329.4 | 0.12 |
| A40 | 12 | 0.10% | 315.2 | 0.09 |
| A40 | 10 | 0.05% | 268.2 | 0.04 |
| A40 | 8 | 0.50% | 156.8 | 0.13 |
| A40 | 8 | 0.40% | 83.6 | 0.22 |
| A40 | 8 | 0.20% | 83.2 | 0.15 |
| A40 | 8 | 0.40% | 72.6 | 0.25 |
| A40 | 8 | 0.30% | 33.2 | 0.48 |
| A40 | 8 | 1.00% | 25.4 | 1.14 |
| A40 | 8 | 2.00% | 25.1 | 1.63 |
| A43 | 8 | 0.05% | 48.0 | 0.13 |
| A45 | 8 | 0.20% | 17.4 | 0.74 |
| A45 | 8 | 1.60% | 16.5 | 2.22 |
| A45 | 8 | 4.40% | 15.9 | 3.80 |
| A45 | 8 | 2.00% | 6.4 | 6.33 |
| A46 | 10 | 0.05% | 73.2 | 0.16 |
| A46 | 8 | 0.05% | 66.6 | 0.10 |
| A46 | 8 | 0.10% | 54.7 | 0.17 |
| A46 | 8 | 0.30% | 50.3 | 0.31 |
| A46 | 8 | 0.80% | 22.4 | 1.15 |
| A46 | 8 | 1.00% | 18.0 | 1.60 |
| A47 | 6 | 0.05% | 12.4 | 0.24 |

TABLE 1. ACSIC TILE CAPACITIES

Nature and Capacity of the Outlet

The outlet for Branch 40A and its branches is JD 414 mainline open ditch with their junction located in SW ¹/₄ of the NW ¹/₄ of Section 19 of Pilot Grove Township in Faribault County. JD 414 open ditch is a 103E public drainage system and it is not anticipated that a permit will be required for this project as it is not classified as a public watercourse.

STATUTE REQUIRED + SUGGESTED EFFORTS

Project Necessity

After due consideration of the present condition of Branch A40 and its branches both observationally and by analysis, Judicial Ditch No. 414 Branch A40 is deemed necessary to improve drainage efficiencies to meet current farming practices and standards. The tiles throughout the watershed are over 100-years old and are deteriorating due to their age and shallow depth.

Environmental, Land Use, and Multipurpose Water Management Considerations (Section 103E.015, Subd. 1)

The Drainage Code requires that the drainage authority assess the necessity and feasibility of a drainage project in relation to the environmental, land use, and multipurpose water management criteria of Section 103E.015, Subd. 1. To assist in providing thoroughness and clarity, the law will be used as the outline for this portion of the report.

103E.015 CONSIDERATIONS BEFORE DRAINAGE WORK IS DONE.

Subdivision 1. Environmental, land use, and multipurpose water management criteria. Before establishing a drainage project, the drainage authority must consider each of the following criteria:

(1) private and public benefits and costs of the proposed drainage project;

The drainage project will decrease the amount and duration of standing water of farm fields, therefore reducing the potential for crop loss and increasing the farmability of within watershed. The improvements to the drainage system will replace failing infrastructure to meet today's farming need for drainage.

Since the present project is on a public drainage system the financial cost will be borne by the benefitted landowners. The only costs that might be paid by the public would be those that are provided through grants or loans.

Storage options are included in preliminary phases of the improvement that will provide protection from increased flooding in downstream waters and adjacent lands and, improve water quality while improving the drainage for benefitted landowners.

(2) alternative measures, including measures identified in applicable state-approved and locally adopted water management plans, to:

The following water management plans were consulted to see what alternative measures might be applicable to the proposed drainage project:

Faribault County Local Water Management Plan 2018-2027

Martin County Local Water Plan 2017-2026

- (i) conserve, allocate, and use drainage waters for agriculture, stream flow augmentation, or other beneficial uses;
- (ii) reduce downstream peak flows and flooding;
- (iii) provide adequate drainage system capacity;
- (iv) reduce erosion and sedimentation; and
- (v) protect or improve water quality;

Both Faribault and Martin County water plans have goals to reduce the impacts of altered hydrology and call out strategies which include implementation of wetland restorations, controlled drainage, storage basins, and other multipurpose drainage management practices. Through this project, a storage basin is being recommended for implementation to minimize impacts to downstream waters. The storage basin will help to reduce peak flows, provide additional water holding capacity within the drainage system, and allow for storage and treatment of tile drainage water. This project aligns with the goals and implementation strategies outlines in local water management plans.

(3) the present and anticipated land use within the drainage project or system, including compatibility of the project with local land use plans;

The present land use for the system is primarily agricultural. Minimal land use change is expected. It is recommended that 1-acre of farmland be converted into a storage pond at the outlet of Branch A40. The storage pond will be seeded with native seed-mix conducive to withstand the expected hydric conditions of the pond providing wildlife habitat to the watershed aligning with the county water plans.

(4) current and potential flooding characteristics of property in the drainage project or system and downstream for 5-, 10-, 25-, and 50-year flood events, including adequacy of the outlet for the drainage project;

Martin - Faribault County Judicial Ditch No. 414 Branch A40 Preliminary Engineers Report

The present and proposed improvement conditions were modeled with XP SWMM. XP SWMM is a fully dynamic modeling software that combines 1-dimensional flow calculations (open channel, pipe flow, ect.) with 2-dimensional flow calculations (floodplain, overland flow, etc.) to better analyze hydrologic and hydraulic conditions. The 1D aspect incorporates land use, soil type, topography, and the associated 2D components to simulate overland and floodplain flow associate with the triggered runoff from a watershed.

Design storms and rainfall data used to generate Type II rainfall distributions for the project area were obtained from the National Oceanic and Atmospheric Administration (NOAA's) Atlas 14 precipitation frequency estimates. Runoff calculations in the model were preformed using TR-55 method. Curve numbers for the project area were determined using GIS soil and land use data. A model was developed for the 2, 5, 10, 25, 50, and 100-year rainfall events for a 24-hour storm duration.

The XP SWMM model compares the legal condition to the proposed improvement for Branch A40 and its branches on JD 414. Three improvement options are being considered during the preliminary phase of this project. All options will include improving drainage tiles to a 0.50 in/day drainage coefficient. Option 1 will include no additional storage, Option 2 will incorporate a 1-acre storage pond, and Option 3 will incorporate a 3-acre storage pond. The options will be compared to show the difference in cost, benefit, and peak flows to downstream waters. Table 2 below summarizes the peak flow rates at the Branch A40 outlet into JD 414 and at the overall outlet of JD 414.

| | | | ear | - | ear | - | /ear | | /ear | | Year | | Year |
|------------|-------------------|------------|----------|------------|----------|------------|----------|------------|----------|------------|----------|------------|----------|
| | | Flow (cfs) | % Change |
| Existing | Branch A40 Outlet | 9.8 | NA | 24.9 | NA | 36.9 | NA | 68.4 | NA | 90.6 | NA | 110.6 | NA |
| Existing | JD 414 Outlet | 260 | NA | 528 | NA | 760 | NA | 1110 | NA | 1410 | NA | 1760 | NA |
| Option 1 | Branch A40 Outlet | 37.6 | 284% | 40.6 | 63% | 45.8 | 24% | 72.7 | 6% | 107.1 | 18% | 134.1 | 21% |
| No Storage | JD 414 Outlet | 287.8 | 11% | 543.7 | 3% | 768.9 | 1% | 1114.3 | 0% | 1426.5 | 1% | 1783.5 | 1% |
| Option 2 | Branch A40 Outlet | 17.9 | 83% | 22.6 | -9% | 33.1 | -10% | 44.2 | -35% | 55.9 | -38% | 115.9 | 5% |
| 1ac Pond | JD 414 Outlet | 268.1 | 3% | 525.7 | 0% | 756.2 | 0% | 1085.8 | -2% | 1375.28 | -2% | 1765.3 | 0% |
| Option 3 | Branch A40 Outlet | 12.4 | 27% | 15.4 | -38% | 18.9 | -49% | 34.5 | -49% | 57.77 | -36% | 113.9 | 3% |
| 3ac Pond | JD 414 Outlet | 262.6 | 1% | 518.5 | -2% | 742.1 | -2% | 1076.2 | -3% | 1377.19 | -2% | 1763.3 | 0% |

TABLE 2: PEAK FLOW RATE COMPARISONS

The increases in peak flowrates from the Branch A40 outlet show large increase in peak flow rate percentages. However this number is skewed as the Branch A40 watershed is small in nature and low peak flowrates exit the system. As a result, even small numerical differences in peak flowrates show a large percentage increase. Therefore, the outlet peak flowrate comparison used the combined flows from the JD 414 open ditch for a more accurate depiction on the impacts to the outlet of the system.

Option 1 implements the improvement with no additional storage incorporated into the system. When comparing the peak flowrates to the legal system, there is notable increase of peak flow rates on the 2-year and 5-year storm events with increases at the outlet of JD 414 open ditch of 11% and 3% respectively. For the 10-year through 100-year storm events the peak flow increases range from 0-1% increase which can be considered negligible at the JD 414 open ditch outlet.

Option 2 implements a 1-acre storage pond to offset increase for peak flows. The goal of the storage pond was to target reducing the 2-year and 5-year storm events as they produced increases from the improvement. When comparing the peak flowrates to the legal system, the peak flow rates for the 2-year storm event increased 3% at the outlet of JD 414 open ditch and had reduced or had no increase on flowrates at the JD 414 open ditch outlet for the remaining storm events modeled. This option nearly matches the outlet peak flowrates into JD 414 for the 2- through 100-year events and would be cost effective for a watershed of this size.

Option 3 implements a 3-acre storage pond to offset increase in peak flows. The goal of the 3-arce storage pond was to best match or reduce peak flows at the JD 414 open ditch outlet on all storm events. The 3-acre storage pond produced the same or reduced peak flowrates at the outlet of the JD 414 open ditch outlet for all events. However, a pond of this size for this size of watershed may not be cost effective based on recent improvement projects. Outside funding would likely be necessary to incorporate a pond of this size to make the overall project cost effective.

(5) the effects of the proposed drainage project on wetlands;

Drainage projects must comply with a variety of state and federal wetland regulations: USACOE 404, Minnesota Wetland Conservation Act, and USDA Swampbuster. A Level 1 wetland delineation was completed in areas where improvements are slated to take place. Where tile improvements encroach identified wetland areas, non-perforated tile and water tight connections will be utilized. Connections of existing private tiles will not be enlarged with the improvement in these areas. Therefore, there are no anticipated effects on wetland with this improvement.

(6) the effects of the proposed drainage project on water quality;

Water quality issues pertinent to drainage projects can include erosion and sediment transport potential, and non-point pollution. After checking available TMDL information and the MPCA Impaired Waters listing, its notes that JD 414 east of the county boundary, County Road 342, is impaired for macroinvertebrate bioassessments. The utilization of drainage will not decrease the water quality of existing conditions to macroinvertebrates.

The proposed storage pond options with add detention and will also provide sediment and nutrient trapping which increases overall quality of water exiting JD 414 Branch A40. The sediment trap in the proposed storage pond will retain sediment, keeping it from going downstream with proper maintenance.

Please refer to the multipurpose drainage management plan map in Appendix D for additional water quality and best management practices. The multi-purpose drainage management plan was shared with landowners for implementation of preventative, control, and treatment measures. The respective county Soil and Water Conservation Districts can assist landowners with implementation and funding as many of the practice are out of the jurisdiction of the drainage authority. A 1-acre storage pond is recommended with the project that will increase water quality at the outlet of the Branch A40 tile watershed. Other preventative practices can be incorporated throughout the watershed on a private landowner basis to further improve water quality and soil health.

(7) the effects of the proposed drainage project on fish and wildlife resources;

The proposed drainage project will not have any impacts on fish and wildlife resources as no landscapes changes of this nature will occur. The implementation of a storage pond will provide additional wildlife habitat within the watershed if incorporated.

(8) the effects of the proposed drainage project on shallow groundwater availability, distribution, and use; and

There is no anticipated effect of the proposed project shallow groundwater; the project should only impact the soil saturation levels. There are no known irrigation or personal wells located close enough to the ditch to be effected by drainage tiles.

(9) the overall environmental impact of all the above criteria.

The project will have negligible environmental impacts, as there are no major land use changes, wetland impacts, fish and wildlife habitat changes or any adverse effects to water quality. Land use changes include conversion of farmland to construct a 1-acre storage and treatment pond. The implementation of storage with the improvement will provide storage and treatment to the watershed and additional wildlife habitat. The project as recommended will have negligible effects to downstream waters and downstream water quality.

Statement of Necessity and Feasibility, Section 103E.015, Subd. 1,

After assessing the necessity and feasibility of this drainage project on behalf of the Martin – Faribault Joint Drainage Authority in relation to the environmental, land use, and multipurpose water management criteria of Section 103E.015, Subd. 1, the engineer deems the proposed project to be both necessary and feasible.

Substantial Affect on Public Waters

Upon filing of the Preliminary Engineers Report (PER) to the respective county auditors, the Engineer mailed a physical copy of the PER to the Director of the Division of Ecological and Water Resources of the DNR and an electronic copy to the respective DNR regional office for preparation of the Commissioner Preliminary Advisory Report. Items in the Commissioners Preliminary Advisory Report will be addressed in a response letter or during the Preliminary Hearing.

If the project moves forward, it is expected that no permit will be needed as the improvement outlets into a 103E public drainage ditch that is not listed as a public watercourse.

PROPOSED PROJECT

The following project has been proposed in response to the Petition with due regard to the results of the Preliminary Survey:

While alternatives will be analyzed, there are certain things that will, by necessity, characterize any configuration of the proposed drainage project.

COEFFICIENT OF DRAINAGE

The capacity of agricultural drainage is expressed as a drainage coefficient which is defined as the depth of water over the entire area of the upstream watershed that a tile or ditch can drain in a 24-hour period (inches per day (in/day)). For Branch A40 and its branches, a drainage coefficient of 0.50 in/day for tile is recommended with timing further influencing design.

SYSTEM DEPTH

The depth of Branch A40 and its branches are controlled by three criteria: 1. Provide a minimum of five feet of cover in low spots along public tile alignments, 2. Increase tile grades to improve capacity, and 3. Provide deeper outlets for private tile.

EROSION CONTROL

Required temporary erosion control will consist of silt fence or bio-roll around all drop intakes, ponds and ditches until vegetation is established. The temporary erosion control will be maintained throughout the construction process according to the Minnesota Pollution Control Agency (MPCA) regulations.

Permanent erosion control will consist of riprap around all tile outlets into ditches and ponds as necessary. Seeding and erosion control blanket will be placed on all disrupted areas around road crossings. All disturbed vegetation throughout the project will be reseeded with the appropriate seed mix and mulch.

A Storm Water Pollution Prevention Plan will be developed before final construction plans are complete and a National Pollution Discharge and Elimination System (NPDES) permit application will be filed before construction.

TILE AND CONNECTION MATERIALS

All public tile is non-perforated dual wall HDPE or RCP pipe. Per ISG construction specifications, watertight connections and fittings are required for all drainage tile installation.

TILE REPLACEMENT AND CONNECTIONS

When tiles are replaced, whether through repair or improvement proceedings, the replaced tiles are left in the ground and are segmented. The segments are then used as headers for private tiles. Segments are connected to the replacement tile at property lines and before the tile outlets. The replaced tile will be the responsibility of the landowner into the future. See connection detail on Sheet 4 in the Preliminary Plans.

Project Components

Systems can be all ditch, all tile, or a combination of the two. Each project will, therefore, have its own list of components. The improvement to Branch A40 and its branches will have the following components:

TILE

This drainage project proposes to improve Branch A40 and its branches by enlarging and deepening tile. The proposed tile sizes and its corresponding drainage coefficient are noted below in Table 3. Branches included in the improvement included Branch A40 and its branches A43, A45, A46, and A47. All tiles were sized to provide a drainage coefficient of 0.50 in/day. In some locations, the improvement may cause the proposed drainage coefficient to exceed 0.50 in/day. The most common reasons for this is the limited availability of dual wall pipe sizes and the necessity for the county tile to act as a header for private tile. Due to this some of the smaller branches the drainage coefficient often exceeds the 0.50 in/day recommendation values. However, during high flows the outlet of each branch will control the flow.

TABLE 3: PROPOSED TILE CAPACITIES

| Branch | ACSIC Size (in) | Proposed Size (in) | ACSIC Slope (%) | Proposed Slope (%) | Drainage Area (Acres) | ACSIC Drainage Coefficient (in/day) | Proposed Drainage Coefficient (in/day) |
|--------|--------------------|-----------------------|--------------------|-----------------------|-----------------------------|--|---|
| A40 | 14 | 24 | 0.20% | 0.15% | 427.4 | 0.13 | 0.49 |
| A40 | 12 | 24 | 0.20% | 0.15% | 329.4 | 0.12 | 0.63 |
| A40 | 12 | 24 | 0.10% | 0.10% | 315.2 | 0.09 | 0.54 |
| A40 | 10 | 24 | 0.05% | 0.10% | 268.2 | 0.04 | 0.64 |
| A40 | 8 | 18 | 0.50% | 0.10% | 156.8 | 0.13 | 0.51 |
| A40 | 8 | 15 | 0.40% | 0.10% | 83.6 | 0.22 | 0.58 |
| A40 | 8 | 15 | 0.20% | 0.10% | 83.2 | 0.15 | 0.59 |
| A40 | 8 | 12 | 0.40% | 0.20% | 72.6 | 0.25 | 0.52 |
| A40 | 8 | 8 | 0.30% | 0.50% | 33.2 | 0.48 | 0.61 |
| A40 | 8 | 8 | 1.00% | 0.50% | 25.4 | 1.14 | 0.80 |
| A40 | 8 | 8 | 2.00% | 0.50% | 25.1 | 1.63 | 0.81 |
| A43 | 8 | 15 | 0.05% | 0.05% | 48.0 | 0.13 | 0.72 |
| A45 | 8 | 8 | 0.20% | 0.20% | 17.4 | 0.74 | 0.74 |
| A45 | 8 | 8 | 1.60% | 1.00% | 16.5 | 2.22 | 1.75 |
| A45 | 8 | 8 | 4.40% | 2.50% | 15.9 | 3.80 | 2.86 |
| A45 | 8 | 8 | 2.00% | 2.50% | 6.4 | 6.33 | 7.08 |
| A46 | 10 | 18 | 0.05% | 0.05% | 73.2 | 0.16 | 0.77 |
| A46 | 8 | 15 | 0.05% | 0.05% | 66.6 | 0.10 | 0.52 |
| A46 | 8 | 15 | 0.10% | 0.05% | 54.7 | 0.17 | 0.63 |
| A46 | 8 | 10 | 0.30% | 0.30% | 50.3 | 0.31 | 0.57 |
| A46 | 8 | 8 | 0.80% | 0.75% | 22.4 | 1.15 | 1.12 |
| A46 | 8 | 8 | 1.00% | 0.75% | 18.0 | 1.60 | 1.39 |
| A47 | 6 | 8 | 0.05% | 0.05% | 12.4 | 0.24 | 0.52 |

DROP INLET

A drop inlet is a structure used along a tile to aid in televising tile, accessing the tile to check for sediment accumulation, and draining surface water. Drop inlets are also utilized for connection to the existing public tile or for private tile connection. They are installed periodically along tile alignments, generally in low areas and/or on each side of road crossings. They are also placed at property lines and as replacements for existing drop intakes.

Standard drop inlets are designed to provide surface drainage through slotted intakes during low flow events. The slots are cut in each rib from 10-inches above grade to as much as 4-feet below grade (surrounded with rock in order to promote sedimentation and infiltration). During high flow events, a standard surface inlet trash rack provides an overflow in order to prevent extensive flooding.

When located in a road ditch, water quality inlets may be provided in lieu of a standard drop inlet. Water quality inlets are designed to provide surface drainage infiltration through a washed rock filter during low flow events. This allows for increased settling of sediment and provides an opportunity for nutrient uptake prior to surface runoff entering the tile system. An integrated slotted (or perforated) intake provides an overflow during high flow events, preventing extensive flooding similar to a standard drop intake. With the existing mainline and branch tile lines remaining in place, the new mainlines and branch tiles may not be constructed

Martin - Faribault County Judicial Ditch No. 414 Branch A40 Preliminary Engineers Report

through the lowest point of road ditches or fields. To assure proper drainage, water quality intakes will be offset into these low areas.

STORAGE

Drainage improvements can increase flows, change timing of flows, and increase flooding downstream. Storage is recommended for the project to mitigate these effects. There are three types of storage that can be used on a public drainage system: 1. Onditch storage where the ditch is expanded (widened) and the resulting pond is controlled by a reduced size culvert or control structure. 2. On-tile storage where the tile is removed within the pond. This pond type is controlled by a structure as well. 3. Offditch storage where the pond is constructed to one side of the ditch. The storage pond designed for the JD 414 Branch A40 drainage system utilized on tile storage where the upstream tile will outlet into the pond for temporary storage. The pond will then outlet into the open ditch.

Three options in the preliminary phase of the improvement to Branch A40 and its branches. Option 1 implements the tile improvements with no additional storage incorporated with the project. There are considerable increases to peak flow rates on the 2-year and 5-year storm events.

Option 2 incorporates a 1-acre pond located at the outlet of Branch A40 adjacent to the JD 414 open ditch. The pond is 10.5-feet deep with a storage capacity of 10.5 acre-feet. The pond outlet will be controlled by a 15-inch concrete pipe located at the bottom of the pond, allowing the pond to completely drain during dry periods. The 15-inch outlet pipe matches the size of pipe that can legally be repaired at the outlet of Branch A40 given it is the next available pipe size on the market. The 15-inch pipe will connect into a manhole structure to allow water to overflow during large rain events and enter a larger 24-inch concrete pipe. The 24-inch pipe will outlet into the JD 414 open ditch. The pond inlets and outlets will be armored with riprap to protect from erosion. The 1-acre pond will have a 3% increase on the 2-year storm event and have negligible change on all other storm events. When analyzing the adequacy of the outlet for Branch A40 and its branches, the JD 414 open ditch has capacity to handle a 3% increase in flows for the 2-year event.

Option 3 incorporates a 3-acre pond located at the outlet of Branch A40 adjacent to the JD 414 open ditch. The pond is 10.5feet deep with a storage capacity of 31.5 acre-feet. The pond outlet will be controlled by a 15-inch concrete pipe located at the bottom of the pond, allowing the pond to completely drain during dry periods. The 15-inch pipe will connect into a manhole structure to allow water to overflow during large rain events and enter a larger 24-inch concrete pipe. The 24-inch pipe will outlet into the JD 414 open ditch. The pond inlets and outlet will be armored with riprap to protect from erosion. The 3-acre pond will maintain or decrease flows for all rain events.

It's recommended that Option 2, a 1-arce storage pond, be implemented with the tile improvements to Branch A40 and its branches. When analyzing the improvement without storage the 2-year and 5-year events are the events that are increased by the improvement, and therefore storage should be included and sized to mitigate the peak flow rates for these events. The 1-acre pond maintains or reduces peak flow rates for all storm events except for the 2-year storm event where there is a 3% increase. The JD 414 open ditch has adequate capacity to handle the increase for the 2-year event. Option 3 maintains or reduces the peak flow rates for all storm events approximately \$124,040 more. If PER is approved, viewers will be appointed to analyzed the monetary benefits of the improvement. It is anticipated that the costs will not out-weight the benefits for the improvement when implementing a 3-arce pond without the contribution of outside funding.

Preliminary Cost Estimates

The preliminary estimated construction cost for improvement to Branch A40 and its branches is approximately \$512,976 as outlined in Option 1. Option 2 and Option 3 include the cost for storage and cost \$605,064 and \$729,104 respectively. Per Minnesota state statue, the road authority is charged with the duty of maintaining the crossing of drainage systems. Therefore, costs are included as such in the preliminary cost estimates to the county and township road authorities for tile crossings at County Road 2 and 310th Street. Cost estimates assume boring tile under paved county roads and open cutting gravel township roads.

Detailed cost estimates of the improvement and separable maintenance are included in Appendix F and are summarized below in Table 4. Unit prices were estimated based on recent projects with similar scale and scope of work. Unit prices for standard tile installation were assumed to use High Density Polyethylene (HPDE) pipe and steel pipe for all borings under paved roadways.

Separable Maintenance

When proposing to do an improvement and a separable portion of a larger system is in need of repair, the drainage statute, Section 103E.215, Subd. 6, allows the separation of the cost of repair from the cost of the improvement project. Separable maintenance can be applied to the portions of the existing system that will be replaced or improved by the proposed project. Based on previous projects, the proposed improvement to Branch A40 and its branches described in this report are cost effective and the benefits should outweigh the costs when separable maintenance is considered.

| OPTION 1 - TILE IMPROVEMENT | | | | | | | |
|---------------------------------|---------------|---|---------|---------|----|-----------|--|
| Area | | Separable Improvement Maintenance Cost | | - | | Net Cost | |
| Branch A40 Tile | \$ | 230,091 | \$ | 332,751 | \$ | 102,661 | |
| Branch A43 Tile | \$ | 25,787 | \$ | 33,372 | \$ | 7,586 | |
| Branch A45 Tile | \$ | 25,653 | \$ | 27,561 | \$ | 1,908 | |
| Branch A46 Tile | \$ | 58,117 | \$ | 70,993 | \$ | 12,876 | |
| Branch A47 Tile | \$ | 12,409 | \$ | 17,827 | \$ | 5,418 | |
| Subtotal without Road Crossings | \$ | 352,056 | \$ | 482,504 | \$ | 130,448 | |
| Road Authority Cost | \$ | 11,292 | \$ | 11,292 | \$ | - | |
| Damages Paid To Road Authority | \$ | 6,902 | \$ | 26,773 | \$ | 19,870.20 | |
| Total | \$ | 370,251 | \$ | 520,568 | \$ | 150,318 | |
| | ndowner Costs | \$ | 509,277 | | | | |
| Net Costs | | | | | | 150,318 | |
| Viewers Costs | | | | | | 3,000.00 | |
| | \$ | 512,277 | | | | | |

TABLE 4: PRELIMINARY COST ESTIMATE

| OPTION 2 - TILE IMPROVEMENT W/ 1-AC STORAGE | | | | | | | |
|--|--------------------------|---------|---------------------|----------------|----------|-----------|--|
| Area | Separable Maintenance | | Improvement Cost | | Net Cost | | |
| Tile Improvement | \$ | 352,056 | \$ | 482,504 | \$ | 130,448 | |
| Storage - 1 AC | \$ | - | \$ | 92,087 | \$ | 92,087 | |
| Subtotal without Road Crossings | \$ | 352,056 | \$ | 574,591 | \$ | 222,535 | |
| Road Authority Cost | \$ | 11,292 | \$ | 11,292 | \$ | - | |
| Damages Paid To Road Authority | \$ | 6,902 | \$ | 26,773 | \$ | 19,870.20 | |
| Total | \$ | 370,251 | \$ | 612,656 | \$ | 242,405 | |
| | | Subto | tal L | andowner Costs | \$ | 601,364 | |
| Net Costs | | | | | | 242,405 | |
| Viewers Cost | | | | | | 3,000.00 | |
| Total Project Costs for Landowners | | | | | | 604,364 | |

| OPTION 3 - TILE IMPROVEMENT W/ 3-AC STORAGE | | | | | | | |
|---|--------------------------|----------------|---------------------|--------------|----------|-----------|--|
| Area | Separable Maintenance | | Improvement Cost | | Net Cost | | |
| Tile Improvement | \$ | 352,056 | \$ | 482,504 | \$ | 130,448 | |
| Storage - 3 AC | \$ | - | \$ | 216,128 | \$ | 216,128 | |
| Subtotal without Road Crossings | \$ | 352,056 | \$ | 698,632 | \$ | 346,575 | |
| Road Authority Cost | \$ | 11,292 | \$ | 11,292 | \$ | - | |
| Damages Paid To Road Authority | \$ | 6,902 | \$ | 26,773 | \$ | 19,870.20 | |
| Total | \$ | 370,251 | \$ | 736,696 | \$ | 366,445 | |
| | andowner Costs | \$ | 725,404 | | | | |
| Net Costs | | | | | | 366,445 | |
| | | | | Viewers Cost | \$ | 3,000.00 | |
| | Tota | I Project Cost | s for | Landowners | \$ | 728,404 | |

The preliminary costs estimates for Options 1 and 2 are considered practicable and feasible for an improvement of this size. Option 3 may not be cost effective without outside funding give the cost of the storage pond compared to the watershed size.

Martin – Faribault County Judicial Ditch No. 414 Branch A40 Preliminary Engineers Report SUMMARY OF FINDINGS, CONCLUSIONS + RECOMMENDATIONS

After review, the existing Branch A40, A43, A45, A46, and A47 were determined to have lower capacities than the recommended 0.50 in/day to meet today's standard of farming. The system is approximately 110-years old, which is the life expectancy of tile systems like that of Branch A40 and its branches. This improvement would be a public benefit and contribute to the public welfare of this area.

Branch A40 and its branches tiles will be increased in size to increase drainage capacity to reduce flooding extends and duration of standing water within the watershed. The improvement modeled the hydrology and hydraulics of the watershed and compared it to the existing condition of the system. Three options are considered during the preliminary phase of the improvement. The option include: 1. No storage 2. 1-acre storage pond, and 3. 3-acre storage pond. The 1-acre storage basin is the most cost effective and feasible option for the improvement and is recommended by the Engineer.

In accordance with Section 103E.245, Subd. 1: Whereas the engineer has examined the petition and order and conducted a preliminary survey and, whereas the engineer has found the proposed drainage project to be necessary due to problems found and clarified during the survey, and whereas the engineer has determined the proposed drainage project is necessary and feasible with reference to the environmental, land use, and multipurpose water management criteria in section 103E.015, subdivision 1 and, whereas the engineer determined that the proposed drainage project *does not* substantially affect Public Waters, and whereas the engineer has examined the nature and capacity of the outlet and any extension of the outlet, therefore the engineer recommends the proposed project (or alternative) to the Drainage Authority for preliminary approval.

Since the engineer finds the proposed drainage project in the petition is feasible and complies with the environmental, land use, and multipurpose water management criteria in section 103E.015, Subdivision 1, the engineer has in accordance with Section 103E.245, Subd. 4 included a set of preliminary plans of the drainage project in Appendix A.

PRELIMINARY PLANS

The Preliminary Plans are provided in Appendix A in keeping with Section 103E.245, Subd. 4. They are preliminary plans and are therefore unsigned as signed construction plans are not required at this phase of the project.

Appendix A: Preliminary Plans

G Architecture + Engineering + Environmental + Planning

MARTIN-FARIBAULT COUNTY JUDICIAL DITCH No. 414 BRANCH A40 IMPROVEMENT

MARTIN-FARIBAULT COUNTY, MINNESOTA PRELIMINARY ENGINEERING REPORT

15 WATERSHED BOUNDARY QUARTER SECTION LINE RIGHT OF WAY LINE PROPERTY / LOTHINE WETLAND BOUNDARY EXISTING OPEN DITCH 20 26 Martin Fairm Faribault County OVERHEAD ELECTRIC County UNDERGROUND ELECTRIC UNDERGROUND TELEPHONE 22 UNDERGROUND TV OVERHEAD UTILITY UNDERGROUND UTILIT 37 1 1 UNDERGROUND FIRER OPTIC CONTOUR (MAJOR) CONTOUR (MINOR) CONFEROUS TREE 12 PROJECT LOCATION -PROPOSED OPEN DITCH LOCATION MAP

- TITLE
- 3 DETAILS
- 4 DETAILS 5 DETAILS
- 6 DETAILS
- 7 EXISTING OVERALL
- 8 PROPOSED OVERALL

ERECTED, CLEANED AND CONDITIONED ACCORDING TO MANUEACTURERS' INSTRUCTIONS IN CASE OF DISCREPANCIES BETWEEN MANUFACTURERS' INSTRUCTIO AND THE CONTRACT DOCUMENTS, NOTIFY BY THE ARCHITECT/ENGINEER. ARCHITECT/ENGINEER BEFORE PROCEEDING WITH THE WORK ALL DISSIMILAR METALS SHALL BE EFFECTIVELY ISOLATED FROM EACH OTHER TO AVOID GALVANIC AND COMPLETE COORDINATION OF ALL WORK CORROSION WRITTEN DIMENSIONS TAKE PRECEDENCE OVER THE LOCATION AND TYPE OF ALL INPLACE LITILITIES. SHOWN ON THE PLANS ARE FOR GENERAL INFORMATION ONLY AND ARE ACCURATE AND COMPLETE TO THE BEST OF SCALED DIMENSIONS. NOTIFY ARCHITECT/ENGINEER OF ANY DISCREPANCIES OR CONDITIONS REQUIRING INFORMATION OR CLARIFICATION BEFORE PROCEEDING WITH THE WORK. THE KNOWLEDGE OF I & S GROUP, INC, (ISG), NO WARRANT OR GUARANTEE IS IMPLIED. THE CONTRACTOR SHALL VERIE THE SIZES, LOCATIONS AND ELEVATIONS OF ALL INPLACE 4. FIELD VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS. NOTIFY ARCHITECT/ENGINEER OF ANY UTILITIES PRIOR TO CONSTRUCTION. CONTRACTOR SHALL DISCREPANCIES OR CONDITIONS REQUIRING INFORMATION IMMEDIATELY NOTIFY ENGINEER OF ANY DISCREPANCIES OF OR CLARIFICATION BEFORE PROCEEDING WITH THE WORK. VARIATIONS FROM PLAN. 5. DETAILS SHOWN ARE INTENDED TO BE INDICATIVE OF THE CONTRACTOR IS TO CONTACT "GOPHER STATE HE PROFILES AND TYPE OF DETAILING REQUIRED ONE CALL" FOR UTILITY LOCATIONS, MINIMUM 2 BUSINESS. THROUGHOUT THE WORK. DETAILS NOT SHOWN ARE SIMILAR DAYS PRIOR TO ANY EXCAVATION / CONSTRUCTION IN CHARACTER TO DETAILS SHOWN, WHERE SPECIFIC (1-800-252-1166). DIMENSIONS, DETAILS OR DESIGN INTENT CANNOT BE DETERMINED, NOTIFY ARCHITECT/ENGINEER BEFORE PROCEEDING WITH THE WORK SPECIFICATIONS REFERENCE **B.M. ELEVATION = 1161.22** ALL CONSTRUCTION SHALL COMPLY WITH THE MARTIN COUNTY 48.78 FEET WEST OF CR 53 24.04 FEET S/SW OF N END OF CULVERT WATERMAIN AS PROPOSED BY THE CITY ENGINEERS ASSOCIATION OF MINNESOTA 2013, UNLESS DIRECTED 1.5 FEET EAST OF WITNESS POST PROJECT DATUM TOPOGRAPHIC SURVEY THIS PROJECT'S TOPOGRAPHIC SURVEY CONSISTS OF DATA COLLECTED IN SEPTEMBER-OCTOBER

OWNER - CONTRACTOR AGREEMENT. THE PROJECT MANUAL (WHICH INCLUDES GENERAL SUPPLEMENTARY CONDITIONS AND SPECIFICATIONS), DRAWINGS OF ALL DISCIPLINES AND ALL ADDENDA, MODIFICATIONS AND CLARIFICATIONS ISSUED SUBCONTRACTORS BY THE GENERAL CONTRACTOR IN COMPLETE SETS IN ORDER TO ACHIEVE THE FULL EXTENT ALL CONSTRUCTION SHALL COMPLY WITH THE MARTIN COUNT REQUIREMENTS AND MNDOT STANDARD SPECIFICATIONS FOR CONSTRUCTION, 2018 EDITION, AND THE STANDARD SPECIFICATIONS FOR SANITARY SEWER, STORM DRAIN AND IN U.S. SURVEY FEET. ELEVATIONS HAVE BEEN REFERENCED TO THE NORTH

1. ALL WORK SHALL CONFORM TO THE CONTRACT DOCUMENTS, WHICH INCLUDE, BUT ARE NOT LIMITED TO, THE EQUIPMENT SHALL BE APPLIED, INSTALLED, CONNECTED, 2 CONTRACT DOCUMENTS SHALL BE ISSUED TO ALL HORIZONTAL COORDINATES HAVE BEEN REFERENCED TO THE NORTH AMERICAN DATUM OF 1983 (NAD83), 1996 ADJUSTMENT (NAD83(1996)) ON THE MARTIN COUNTY COORDINATE SYSTEM,

PROJECT INDEX:

OWNER: MARTIN-FARIBAULT JOINT DRAINAGE AUTHORITY **OWNER NAME: MIKE FORSTNER OWNER ADDRESS: 201 LAKE AVENUE,**

PROJECT ADDRESS / LOCATION:

SEC: 25 EAST CHAIN TWP

SEC: 19 & 30 **PILOT GROVE TWP**





ISG

2019 BY ISG.

AMERICAN VERTICAL DATUM OF 1988 (NAVD 88). RTK GPS METHODS WERE USED TO ESTABLISH HORIZONTAI AND VERTICAL COORDINATES FOR THIS PROJECT

OPEN DITCH REPAIR CUI VERT (RCP CULVERT (CMP) TILE TILE (PIPE WIDTH) WATER GAS OVERHEAD ELECTRIC UNDERGROUND ELECTRIC UNDERGROUND TV CONTOUR (MAJOR) CONTOUR (MINOR) DROP INTAKE

LEGEND

CITY LIMITS

SECTION LINE

EASEMENT LINE

WATER EDGE

FENCE LINE

CULVERT DITCH TILE

WATER

GAS

PRIVATE TILE

DECIDUOUS TREE

TREE LINE

HYDRANT

EASEMENT

SLOUGH REPAIR

SPOIL PLACEMENT

TREE CLEARING

REMOVE TREE

BUFFFR

DROP INTAKE

POWER POLE

0

-Ò-

Ø

PROPOSED

EXERCISE

 \bigotimes

ACCESS CONTROL

EXISTING

SUITE 201, FAIRMONT, MN 56081

PH: 507-238-3130

ISG PROJECT # 19-23608

SHEET INDEX


2 NOTES AND QUANTITIES

9 BRANCH A40 PLAN & PROFILE 10 BRANCH A40 PLAN & PROFILE 11 BRANCH A40 PLAN & PROFILE 12 BRANCH A43 PLAN & PROFILE 13 BRANCH A45 PLAN & PROFILE 14 BRANCH A46 PLAN & PROFILE 15 BRANCH A47 PLAN & PROFILE

GIS DISCLAIMER:

INFORMATION FOR THE BOUNDARY / LOT LINES, AND UNDERGROUND UTILITIES SHOWN WAS DERIVED PREPARED FOR, OR BE SUITABLE FOR: LEGAL, ENGINEERING, OR SURVEYING PURPOSES.

PROJECT GENERAL NOTES




1


OF 1


GENERAL TILE INSTALLATION NOTES:


- 1. DURING CONSTRUCTION, CONTRACTOR SHALL MAINTAIN A DRAINAGE OUTLET FOR THE ENTIRE JD 414 BRANCH A40 PROJECT AREA.
- 2. ALL PIPE DIMENSIONS REFERENCED IN THE PLANS REFER TO THE INSIDE DIAMETER.
- 3. ALL ROAD SIGNAGE, COORDINATION, AND TRAFFIC CONTROL SIGNAGE SHALL BE INCIDENTAL TO ROAD RESTORATIONS.
- 4. ALL DEWATERING FOR THE PROJECT IS INCIDENTAL.
- 5. UNLESS OTHERWISE NOTED, CONTRACTOR SHALL LIMIT CONSTRUCTION ACTIVITY TO WITHIN A 100-FOOT WIDE SWATH ALONG PROPOSED TILE ALIGNMENTS FOR 24" TILE OR LESS, AND A 150-FOOT SWATH ALONG PROPOSED TILE ALIGNMENTS FOR TILES LARGER THAN 24". THE SWATH NEED NOT BE CENTERED ON THE PROPOSED TILE ALIGNMENT. ALL ACCESS ROADS SHOULD FOLLOW THE PROPOSED ALIGNMENTS. THE SWATH SHALL NOT DISTURB ANY NON-AGRICULTURAL PRIVATE PROPERTY. DISTURBANCE THROUGH ROAD CROSSINGS, ROAD DITCHES, AND GRASS BUFFERS SHALL BE LIMITED TO THE WIDTH OF A TRENCH NECESSARY FOR SAFE CONSTRUCTION PRACTICES, AND MUST BE RE-SEEDED WHERE NEEDED.
- 6. ALL EFFORTS SHALL BE MADE DURING CONSTRUCTION TO SEPARATE SOIL TYPES. BACKFILL SHALL BE COMPACTED PRIOR TO PLACEMENT OF TOPSOIL, EXCEPT THE TOP TWO (2) FEET, FOR WHICH COMPACTION SHALL BE MINIMIZED TO THE EXTENT POSSIBLE. TOPSOIL SHALL BE PLACED TO A MINIMUM DEPTH OF 6", OR UNIFORM TO THE TOPSOIL DEPTH OF THE SURROUNDING AREA. EXCAVATED SPOILS SHALL BE SPREAD EVENLY IN CONSTRUCTION AREA AS TO NOT IMPEDE DRAINAGE. ALL EFFORTS SHALL BE MADE TO KEEP TOPSOIL ON TOP AND SEPARATED. NO TOPSOIL SHALL BE PLACED IN THE TRENCH BELOW 2' FROM EXISTING GROUND UNLESS APPROVED BY THE ENGINEER.
- ALL SPOIL LEVELING, GRADING, AND RESTORATION OF DISTURBED AREAS SHALL BE IN ACCORDANCE TO THE CONTRACT DOCUMENTS AND SHALL BE INCIDENTAL TO THE WORK.
- 8. MISCELLANEOUS TREE CLEARING SHALL BE INCIDENTAL TO TILE INSTALLATION.
- 9. ALL PIPE BEDDING AND ENCASEMENT IS INCIDENTAL TO STANDARD TILE INSTALLATION. REFER TO SPECIFICATIONS FOR DEFINITIONS. FOUNDATION MATERIAL SHALL BE USED IF UNSUITABLE OR UNSTABLE SOILS ARE PRESENT. THE USE OF FOUNDATION MATERIAL SHALL BE APPROVED BY THE ENGINEER BEFORE PLACEMENT.
- 10. UNLESS OTHERWISE NOTED, ALL HDPE BENDS AND FITTINGS SHALL BE INCIDENTAL TO THE TILE PAY ITEMS, MUST BE BANDED, WRAPPED IN FABRIC, AND SURROUNDED WITH CRUSHED ROCK.
- 11. ALL TILE ENDS MUST BE CAPPED TO NOT TAKE SEDIMENT UNLESS ANOTHER TILE (PRIVATE OR PUBLIC) IS CONNECTED INTO THE PROPOSED TILE. CAPPING SHALL BE INCIDENTAL TO TILE INSTALLATION.
- 12. ALL BENDS LARGER THAN 11.25° MUST BE CONSTRUCTED AS PRE-FABRICATED BENDS. ANY BENDS LARGER THAN 45° MUST BE CONSTRUCTED WITH MULTIPLE BENDS WITH AT LEAST 10 FEET IN BETWEEN EACH BEND.
- 13. UNLESS SPECIFICALLY NOTED, HDPE AND RCP WILL BE THE ONLY ACCEPTABLE MATERIALS FOR ALL PROPOSED BURIED TILE. REFER TO SPECIFICATIONS FOR PROPER INSTALLATION REQUIREMENTS.
- 14. VERIFY EXISTING TILE LOCATIONS AND ELEVATIONS PRIOR TO CONSTRUCTION, PAID FOR AS TILE INVESTIGATION. ANY ALIGNMENT CHANGES MADE DUE TO TILE INVESTIGATION SHALL BE APPROVED BY THE ENGINEER DURING CONSTRUCTION. ALL EFFORTS WILL BE MADE TO UTILIZE THE SAME FITTINGS AS DESIGNED AND CONTRACTOR SHALL BE COMPENSATED FOR ADDITIONAL BENDS AND FITTINGS, IF NEEDED.
- 15. DROP INTAKES WILL BE PAID FOR BY EACH AND NO ADDITIONAL COMPENSATION WILL BE MADE FOR IN-FIELD ELEVATIONS THAT VARY FROM THE PLANS. MINOR SHAPING AROUND DROP INTAKES AND CULVERT INLETS SHALL BE INCIDENTAL TO THEIR RESPECTIVE PAY ITEMS.
- 16. DROP INTAKES THAT ARE NOT INTENDED TO TAKE SURFACE FLOW MAY BE CAPPED, AS DETERMINED BY THE ENGINEER. INTAKES MAY BE CUT DOWN AND BURIED AFTER FINAL TELEVISING, PER LANDOWNER REQUEST, AND WILL BE PAID FOR AS "CAP DROP INTAKE".
- 17. DROP INTAKES THAT ARE DESIGNED TO BE ON PROPERTY LINES SHALL BE ADJUSTED IN THE FIELD TO MATCH ACTUAL LOCATION OF PROPERTY LINE.
- 18. AT CROSSINGS OF EXISTING TILE, ONLY THE UPSTREAM SIDE NEED BE CONNECTED, UNLESS OTHERWISE DEEMED NECESSARY. EACH CROSSING WILL BE PAID FOR AS ONE CONNECTION. ALL BENDS, TEES, CONNECTING TILE, AND OTHER FITTINGS NECESSARY FOR CONNECTION SHALL BE INCIDENTAL TO CONNECTION BID ITEM.
- 19. ALL TILE CONNECTIONS MUST BE CONNECTED ON THE SIDE OF THE RECEIVING PIPE. TILE CONNECTIONS CANNOT BE MADE COMPLETELY VERTICAL TO PIPE.
- 20. EXISTING BRANCH CONNECTIONS SHALL BE CONSTRUCTED ONE SIZE LARGER THAN THE EXISTING SIZE, UNLESS OTHERWISE SPECIFIED, WITH DUAL WALL HDPE AND APPROPRIATE FITTINGS. (SINGLE WALL PE TILE WILL NOT BE ALLOWED)
- 21. ALL PRIVATE TILE CONNECTIONS SHALL BE CONSTRUCTED WITH INSERTA-TEE CONNECTIONS OR APPROVED EQUAL, WHERE POSSIBLE. CONNECTING TILE SHALL MATCH EXISTING SIZE AND SLOPE. (PE TILE WILL BE ALLOWED FOR PRIVATE TILE CONNECTIONS ONLY)

| TOTAL ESTIMATED QUANTITIES | | | | | | |
|----------------------------|--|------|-----------------------|--|--|--|
| Item Code | Item | Unit | Estimated Quantity | | | |
| 2021.501 | MOBILIZATION | LS | 1 | | | |
| 2021.601 | TILE INVESTIGATION | HR | 23 | | | |
| 2106.501 | COMMON EXCAVATION (P) (EV) | CY | 65340 | | | |
| 2451.509 | GRANULAR PIPE FOUNDATION | CY | 781 | | | |
| 2501.511 | 24-INCH CLASS III RCP PIPE | LF | 108 | | | |
| 2501.511 | 15-INCH CLASS III RCP PIPE | LF | 72 | | | |
| 2501.515 | 24-INCH RCP APRON | EA | 6 | | | |
| | INSTALL 12-INCH PERFORATED TILE | | | | | |
| 2502.541 | (WATER QUALITY INLET) | LF | 158 | | | |
| 2503.603 | 24-INCH AGRICULTURAL TILE | LF | 4245 | | | |
| 2503.603 | 18-INCH AGRICULTURAL TILE | LF | 700 | | | |
| 2503.603 | 15-INCH AGRICULTURAL TILE | LF | 1758 | | | |
| 2503.603 | 12-INCH AGRICULTURAL TILE | LF | 1220 | | | |
| 2503.603 | 10-INCH AGRICULTURAL TILE | LF | 200 | | | |
| 2503.603 | 8-INCH AGRICULTURAL TILE | LF | 2399 | | | |
| 2506.502 | FURNISH & INSTALL WATER QUALITY INLET | EA | 4 | | | |
| 2506.502 | INSTALL DROP INTAKE (18-INCH) | EA | 15 | | | |
| 2506.502 | CAP DROP INTAKE (18-INCH) | EA | 6 | | | |
| 2506.516 | INSTALL STRUCTURE S-1 WITH GALVINIZED GRATE | LS | 3 | | | |
| 2506.602 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 45 | | | |
| 2506.602 | CONNECT EXISTING 18-INCH TILE | EA | 1 | | | |
| 2506.602 | CONNECT EXISTING 15-INCH TILE | EA | 1 | | | |
| 2506.602 | CONNECT EXISTING 10-INCH TILE | EA | 2 | | | |
| 2506.602 | CONNECT EXISTING 8-INCH TILE | EA | 9 | | | |
| 2506.602 | CONNECT EXISTING 6-INCH TILE | EA | 1 | | | |
| 2506.602 | 15-INCH CROSS-CONNECT W/30 LF OF SPECIFIED PIPE | EA | 1 | | | |
| 2506.602 | 12-INCH CROSS-CONNECT W/30 LF OF SPECIFIED PIPE | EA | 2 | | | |
| 2506.602 | 8-INCH CROSS-CONNECT W/30 LF OF SPECIFIED PIPE | EA | 1 | | | |
| | 24-INCH TILE OUTLET | | | | | |
| 2506.603 | (20 LF OF PIPE & RIPRAP ON GEOTEXTILE FABRIC) | EA | 1 | | | |
| 2511.501 | CLASS III RIPRAP WITH GEOTEXTILE FABRIC | СҮ | 150 | | | |
| | 16.5' BUFFER STRIP SEEDING | 1 | | | | |
| 2575.501 | (SEED MIX: BUFFER BLEND WITH TYPE 3 MULCH) | AC | 1.19 | | | |
| | STANDARD SIDESLOPE SEEDING | | | | | |
| 2575.501 | (SEED MIX: BUFFER BLEND WITH TYPE 8 MULCH) | AC | 1.29 | | | |
| 2575.541 | BUFFER STRIP MOWING | AC | 2.37 | | | |
| 2575.545 | WEED SPRAYING | AC | 3.66 | | | |

















INC. AND MAY NOT BE USED, COPIED OR DUPLICATED WITHOUT PRIOR WRITTEN CONSENT.

PROJECT

MARTIN-FARIBAULT COUNTY

JUDICIAL DITCH No. 414 BRANCH **A40 IMPROVEMENT**

MARTIN-FARIBAULT COUNTY MINNESOTA

| | REVISION SCHEDULE | |
|------|-------------------|----|
| | | |
| DATE | DESCRIPTION | BY |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

19-23608 PROJECT NO. FILE NAME 23608 NOTES & DETAILS DRAWN BY DMP DESIGNED BY BPG **REVIEWED BY** MAO ORIGINAL ISSUE DATE --/--/--CLIENT PROJECT NO. -


TITLE

DETAILS


5


OF 14


SHEET





















| | | DI BR A40-4 R=1130.19 I=1120.66 | -EXISTING SURFACE, TYP. | |
|----------|---------|---|---------------------------------------|--------------------------|
| | FXISTIN | | | |
| | | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | -EXISTING 12" BRANCH A40 |
| (Ε, ΤΥΡ. | | INSTALL 2,850 LF 24" TILE @ 0.10% STA 15+00 TO 43+50 | | |








| THOMPSON, | TODD & MALORIE | |
|--------------------------------------|--|------|
| | | 1160 |
| | NOTE: XXX.XX - EXISTING GROUND & XXX.XXX - PROPOSED TILE INVERT | 1150 |
| ∽.~.eXISTIN0 | SURFACE, TYP, | 1140 |
| | 8" BRANCH A40 TILE (WHEN ENCOUNTERED) | 1130 |
| EXISTING 8" BRANCH A45 | | 1120 |
| 2 LF 8" TILE @ 2.50% 4+00 TO 8+72 | NSTALL 200 LF 8" TILE @ 1.00% STA 2+00 TO 4+00 NSTALL 200 LF 8" TILE @ 0.20% | 1110 |
| 1138.9 1138.25 1128.25 | 1125.75 00+7.01.00+0 VIS 1123.35 1125.55 1125. | |
| 6+00 5+00 4+ | 00 3+00 2+00 1+00 0+00 | 1100 |




| •••• | | •••• | ••••• | ••••• | ••••• | ••••• | ••••• | | · · · · : : · · · · · · · · · · · · · · | •••••• | · · · · · · · · · · · · · · · · · · · | | |
|---|---------------------------------------|--|---|---------------------------------------|---------------------------------------|---|--|--|---|---|---|-----------|--|
| | · · · · · · · · · · · · · | · · · · · · · · · · · · | | · · · · · · · · · · · · | | · · · · · · · · · · · · · | · · · · · · · · · · · · | · · · · · · · · · · · · · · | · · · · · · · · · · · · · | NOTE: | | Ī | |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · | · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · | · · · · · · · · · · · · · | XXX.XX - EXIST | | | |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · | | | · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · | | POSED TILE INV | | |
| · · · · | | ••••• | ••••• | | · · · · · | · · · · · : · · · · | · · · · · : · · · · | • • • • • • • • • • • • | | ////////-TINC | | | |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | •••••• | •••••• | · · · · · · · · · · · · · · · · · · · | •••••• | | | | | | | | |
| | · · · · · · · · · · · · · | · · · · · · · · · · · · · | • • • • • • • • • • • • | • • • • • • • • • • • • | • • • • • • • • • • • • | | • • • • • • • • • • • | | • • • • • • • • • • • • | • • • • • • • • • • • • • | • • • • • • • • • • • • | | |
| · · · · · · · · · · · · · · · · · · · | <mark>.</mark> | · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · | · · · · · · · · · · · · | | · · · · · · · · · · · · · | · · · · · · · · · · · · · | · · · · · · · · · · · · · · · | | |
| | | | | | | | | | | | | | |
| | • • • • • • • • • • • • | • | EXISTIN | NG SURFACE, T | YP, · : · · · · | • • • • • • • • • | • • • • • • • • • | ••••• | ••••• | | | | |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · | · · · · · · · · · · · · | | · · · · · · · · · · · | | · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · | ••••••••••••••••••••••••••••••••••••••• | · · · · · · · · · · · · · · · · · · · | · · · · <u>·</u> · · · · · · | 1 | | ······································ | · · · · · : · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | |
| | | | | | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · | | · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | | |
| | | | • • • • • • • • • • • • | | • • • • • • • • • • | | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | · · · · · · · · · · · · | | | |
| <u> </u> | | | <u> </u> | | <u> </u> | | | | · · · · · · · · · · · · · · · · · · · | | | | |
| <u> </u> | · · · · · · · · · · · · · | <u> </u> | <u></u> | | · · · · · · · · · · · · · · · · · · · | | · · · · · · · · · · · · | | · · · · · · · · · · · · · · · | | | | |
| · · · · · · · · · · · · · · · · · · · | | P INTAKE, TYP | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | CROSS-CON | √NECT:/: | · · · · · · · · · · · · · · · · · · · | | ICH A46 TILE | | |
| | | \mathcal{F} . IN \mathcal{F} \mathcal{F} . \mathcal{F} | ••••••• | · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | :::::::::::::::::::::::::::::::::::::: | 8":TILE: : : : : : | · · · · · · · · · · · · · | WHEN ENC | OUNTERED) | | |
| | PROPOSED | | · · · · · · · · · · · · · · · · · · · | EX | (ISTING 8" BRAN | ICH A46 | | | | | | | |
| : 8" BRANCH | | • • • • • • • • • • | ••••• | | · · · · · · · · · · · · · · · · · · · | | • • • • • • • • • • • • | • • • • • • • • • • • • | • • • • • • • • • • • • | | • • • • • • • • • • • • | | |
| | | · · · · · · · · · · · · · · · · · · · | | | · · · · · · · · · · · · · · · · · · · | | | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | | |
| | · · · · · · · · · · · · · | · · · · · · · · · · · · · | • • • • • • • • • • • | | • • • • • • • • • • • • | INST | ALL 200 LF 10" T | ILE @ 0.30% | | | · · · · · · · · · · · · · · · · · · · | | |
| | | | | | · · · · · · · · · · · · · · · · · · · | STA 11+00 TO 13+00 | | | | | | | |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · | · · · · · · · · · · · · | ••••• | | · · · · · · · · · · · · · · · · · · · | | | | · · · · · · · · · · · · · · · · · · · | | · · · · · · · · · · · · · · · · · · · | | |
| · · · · | NSTALL 500 LF 1 | 5" TILE @ 0.05% | % | | • • • • • • • • • • | | | · · · INSTALL 55 | 7 LF 8" TILE @ 0 | .75% | | | |
| ••••••••••••••••••••••••••••••••••••••• | STA 6+00 | TO 11+00 | | | | | · · · · · · · · · · · · · · · · · · · | STA 2 | 13+00 TO 18+57 | · · · · · · · · · · · · · · · · · · · | | | |
| | | · · · · · · · · · · · · · · · · · · · | • • • • • • • • • • • • | • • • • • • • • • • • | • • • • • • • • • • • • | | | | | | · · · · · · · · · · · · · · · · · · · | | |
| · · · · · · | · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | ••••• | • • • • • • • • • • • • | • • • • • • • | · · · · · · · · · · · · · · · · · · · | | • • • • • • • • • • • • • | • • • • • • • • • • • • | • • • • • • • • • • • • • | | | |
| ι. | | 50 20 | | Ú. | | Ú. | <u>.</u> | ι. | | Ú. | | | |
| 45 | 2.50 | 2-00 | 0 0 7 8 | 2.65 | 00 70 70 | 3.25 | 00 00 00 | 4 75 | 5.50 | 0.22 0.21 | | | |
| 1122 | <u> </u> | <u> </u> | $\sim \sim $ | | $\sim \sim 0.0$ | $\cdots \overline{\mathbf{Q}} \overline{\mathbf{Q}} \cdots$ | <u>5</u> | 24 | <u>2</u> | $\overline{\mathbf{N}}$ | $\underline{\omega}$ | | |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · | · · · · · · · · · · · · · · · | · · · · · · · · · · · · · | · · · · · · · · · · · · | · · · · · · · · · · · · · | · · · · · · ; · · · · · | · · · · · · · · · · · · · · · · · · · | · · · · <u>~</u> ; <u>~</u> · · · · | $\sum_{i=1}^{n} \sum_{j=1}^{n} \sum_{i=1}^{n} \sum_{i$ | · · · · <u>~</u> ; <u>~</u> · · · · | · · · · · · · · · · · · · · · · · · · | | |
| | · · · · · · · · · · · | · · · · · · · · · · · · · | · · · · · · · · · · · · · | · · · · · · ; · · · · · | · · · · · · ; · · · · · | · · · · · · · · · · · · | · · · · · · ; · · · · · · | · · · · · · · · · · · · · · | | · · · · · · · · · · · · · · · · · · · | · · · · ~ ; ~ · · · · · | · · · · t | |
| 7+00 | ~~~ 8+00 | 9+00 | 10+00 | 11+00 | 12+00 | 13+00 | 14+00 | 15+00 | 16+00 | 17+00 | 18+00 | | |



| | • | • | . | |
|-------------------|--|--|---------------------------------------|------|
| | | | | |
| | | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | 1130 |
| | EXISTING 6" BR | ANCH A47 | | |
| | | | f | 1120 |
| | CONNECT EXISTING 8" BRANCH A46 TILE (WHEN ENCOUNTERED) | ROP INTAKE, TYP CONNECT 6" BRANCI (WHEN ENCOL | A47 TILE | 1110 |
| - | INSTALL 509 LF 8" TILE @ STA 0+00 TO 5+09 | 0.05% | | |
| | | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | 1100 |
| 1127.7 1122.72 | •. • •. • | 1122.87 1129.9 1122.92 | 1129.4 | |
| | $\frac{1}{2}$ | | | 1090 |

Appendix B: Order + Petition

G Architecture + Engineering + Environmental + Planning



BLUE EARTH OFFICE: 825 EAST SECOND STREET P.O. BOX 247 BLUE EARTH, MN 56015 TELEPHONE: (507) 526-2196 FAX: (507) 526-3065

MAPLETON OFFICE: 101 SMITH STREET NE MAPLETON, MN 56065 TELEPHONE: (507) 524-4110

BRUCE E. SELLERS SELLERS@WENDLANDLAW.COM

REPLY TO BLUE EARTH OFFICE.

August 2, 2019

John Thompson Faribault County Drainage Manager PO Box 130 Blue Earth, MN 56013

> RE: Improvement Petition for Faribault-Martin County Judicial Ditch No. 414 Our File No.: 3507.01

Dear Mr. Thompson:

Our office represents petitioners for the proposed improvement to Faribault-Martin County Judicial Ditch No. 414, Brach A40 ("J.D. 414" or "the system"). Pursuant to Minn. Stat. §103E.202, enclosed please find the following for filing:

- 1. Petition for Improvement of Faribault-Martin County Judicial Ditch No. 414 ("Petition"):
- 2. A Map referred to and incorporated as "Exhibit A" depicting the starting point and general course and terminus of the proposed improvement project which adequately satisfies the requirement under Minn. Stat. §103E.215. Subd. 4(c)(3): and
- 3. Corporate Surety Bond ("Bond") in the face amount of \$50,000.00 payable to the Drainage Authority of Faribault-Martin County Judicial Ditch No. 414.

All information used to determine the delineation of the watershed boundary for J.D. 414. Branch A40 as depicted on Exhibit A, were obtained from I+S Group engineers ("ISG") using the Surface Water Hydrology Atlas from Minnesota State University-Mankato. current Geographical Information Systems software. Lidar Contour Lines. ArcGIS, and original tile maps received from Faribault and Martin Counties and landowners.

Exhibit A depicts "Tracts" which indicate the number of owners of 40-acre tracts or government lots within the watershed, the boundary of which was also provided by ISG using the ArcGIS software. ArcGIS is a geographic information system that provides the infrastructure for making and working with maps and geographic information by compiling geographic data and analyzing mapped information. The parcel data is provided by Faribault and Martin Counties, and, based on the section information (also provided by the

Qualified Neutral under Rule 114 of Minnesota General Rules of Practice

REAL ESTATE = PROBATE = ESTATE PLANNING = CIVIL LITIGATION = DEFENSE OF PUBLIC ENTITIES = EMPLOYMENT = PRIVATE/PUBLIC DRAINAGE = PERSONAL INJURY = CORPORATE/BUSINESS= CONTRACTS = FAMILY LAW

August 2, 2019 Page | 2

County), the parcel areas are "split" to identify the 40 acre "Tracts", and another software program is used to calculate the parcel area for each "Tract" within the information developed by the ArcGIS. Additionally, I personally cross-referenced the landowner information with the information available through the Faribault and Martin Counties' GIS website and/or using the online Beacon software.

Pursuant to Minn. Stat. §103E.215, Subd. 4(a), a petition is considered to be adequate if it is signed by: (1) at least 26% of the owners of the property affected by the proposed improvements; OR (2) at least 26% of the owners of the property that the proposed improvement passes over; OR (3) the owners of at least 26% of the property area affected by the proposed improvement; OR (4) the owners of at least 26% of the property area that the proposed improvement passes over.

With respect to the adequacy of this Petition as it relates to satisfying the requirements of Minn. Stat. §103E.215, Subd. 4(a), I will address each sub-section of this particular statute.

(1) at least 26 percent of the owners of the property affected by the proposed improvement;

There are a total of 7 owners affected by the proposed improvement benefited or damaged by the project. I have submitted a petition which includes a total of 4 owners (57.14%) of property affected by the proposed improvement.

(2) at least 26 percent of the owners of property that the proposed improvement passes over;

There are a total of 7 owners of property that is bordered by, touched by, or is underneath the path of the proposed drainage project. I have submitted a petition which includes a total of 4 owners (57.14%) of property the proposed improvement "passes over".

(3) the owners of at least 26 percent of the property area affected by the proposed improvement; or

The Faribault-Martin County Judicial Ditch No. 414, Branch A40 watershed benefits a total property area consisting of approximately 445.19 acres. I have submitted a petition which includes a total of 4 owners owning a total of approximately 342.14 acres (76.85%) of the property area affected by the proposed improvement.

(4) the owners of at least 26 percent of the property area that the proposed improvement passes over.

The proposed improvement drainage project borders, touches, or is underneath the path of a total property area consisting of approximately 374.25 acres. I have submitted a petition which includes a total of 4 owners owning a total of approximately 289.23 acres (77.28%) of the property area that the proposed improvement passes over.

Therefore, I believe the petition satisfies the requirements of Minn. Stat. §103E.215, Subd. 4 by containing signatures the owners of (1) at least 26 percent of the owners of the property affected by the proposed improvement; (2) at least 26 percent of the owners of property that the proposed improvement passes over; (3) the owners of at least 26 percent of the property area affected by the proposed improvement; and (4) the owners of at least 26 percent of the property area that the proposed improvement passes over.

August 2, 2019 Page | 3

I have also enclosed a spreadsheet which details the information provided above. After you have had an adequate opportunity to review and verify the information provided, I would request that this Petition be presented to the Faribault-Martin County Joint Board of Commissioners acting as Drainage Authority for Judicial Ditch No. 414.

Chuck Brandel, civil engineer with ISG, has been involved with this proposed improvement project from the initial stages. At the request of the Petitioners, Mr. Brandel provided the preliminary review and feasibility study to landowners for their review and consideration, and that information was used by Petitioners to assist them with their decision to move forward with this Petition. As such, for the sake of convenience and expense, the Petitioners would request that Mr. Brandel and ISG be appointed as engineers for the proposed improvement project.

Please contact me at your earliest convenience if you have further questions, require further information, or believe there are issues that need to be addressed prior to acceptance of the Petition. Thank you in advance for your consideration and prompt attention with this matter.

Sincerely yours,

WENDLAND SELLERS LAW OFFICE

Bruce E. Sellers

Bruce E. Sellers FOR THE FIRM

Enc.

PETITION FOR AN IMPROVEMENT OF FARIBAULT-MARTIN COUNTY JUDICIAL DITCH NO. 414

TO THE FARIBAULT AND MARTIN COUNTY JOINT BOARD OF COMMISSIONERS AS DRAINAGE AUTHORITY IN RELATION TO FARIBAULT-MARTIN COUNTY JUDICIAL DITCH NO. 414 ("DRAINAGE AUTHORITY")

The Petitioners herein respectfully represent:

~

۹,

WHEREAS, this Petition specifically relates to Branch A40 and its subsurface tile laterals, specifically, A41, A43, A45, A46, and A47 (together, "Branches"), of Faribault-Martin County Judicial Ditch No. 414 subsurface tile ("the system") located in Sections 19 and 30 of Pilot Grove Township, Faribault County, and Sections 24 and 25 of East Chain Township, Martin County, with the intention of improving the system by increasing the drainage capacity; and

WHEREAS, the Branches have insufficient capacity or requires enlarging in order to furnish sufficient capacity. Petitioners propose enlarging said Branches and laterals to furnish sufficient capacity thereof ("proposed Improvement Project"); and

WHEREAS, the starting point, general course and terminus of the proposed Improvement Project is depicted on Exhibit A which is attached hereto for reference; and

WHEREAS, Petitioners further request that the engineer be specifically ordered to determine and offer alternative proposals for the consideration of the Drainage Authority which relate to the proposed improvement of the drain capacity of the system that the engineer deems feasible, if any, including repairs to the current mainline open ditch and alternative outlets, if any; and

WHEREAS, Petitioners assert that the proposed Improvement Project will benefit and be useful to the public and will promote the public health; and

WHEREAS, Petitioners recognize that water storage benefits the entire system and requests that the engineer appointed by the Drainage Authority consider water storage designs into the proposed Improvement Project. Petitioners further request and will support actively seeking outside funding for said water storage; and

WHEREAS, a separable part of the drainage system may need repair. Petitioners requests, pursuant to Minn. Stat. §103E.215, subd. 6, that separable maintenance be used for those locations where existing tiles are being replaced with new tile. Petitioner requests that the appointed project engineer be ordered to determine a proportionate share of life span based on the existing condition versus the tiles original designed capacity. It is recommended by Petitioners that the separable maintenance to be paid by the entire system is that percentage of the in-place tile whose life span capacity has been used and that the improvement pay for that percentage of the tile, life span or capacity that still is in repair; and

WHEREAS, Petitioners request the engineer appointed by the Drainage Authority is asked to include in its detailed survey report a statement showing the proportionate estimated cost of the proposed improvement required to repair the separable part of the existing system and the estimated proportionate share of the cost of the added work required for the improvement. The Petitioners, as landowners, request that a percentage be paid as separable maintenance by the entire system and a percentage be paid for by the improvement benefits as determined by the appointed project engineer and viewers; and

WHEREAS, the names and addresses of owners of the property area that the Improvement passes over is depicted on the attached Exhibit A are as follows:

| Tract 1* | |
|---|------------------------------------|
| Owner/Address: | Terry L. & Sonja Peterson |
| | 2927 50th St. |
| | Blue Earth, MN 56013 |
| Tract 2 | |
| Owner/Address: | Terry L. & Sonja Peterson |
| | 2927 50th St. |
| in the second | Blue Earth, MN 56013 |
| Tract 3 | |
| Owner/Address: | Robert F. & Janet L. Cone |
| | 389 Lake Aires Rd. |
| | Fairmont, MN 56031 |
| | |
| Tract 4* | |
| Owner/Address: | James & Ronda Cone Trust Agreement |
| | James & Ronda Cone, Trustees |
| | 640 W Interlaken Rd. |
| · · · · · · · · · · · · · · · · · · · | Fairmont, MN 56031 |
| Tract 5* | |
| Owner/Address: | James & Ronda Cone Trust Agreement |
| | James & Ronda Cone, Trustees |
| | 640 W Interlaken Rd. |
| | Fairmont, MN 56031 |
| Tract 5 | |
| Owner/Address: | Robert F. & Janet L. Cone |
| | 389 Lake Aires Rd. |
| | Fairmont, MN 56031 |

| Tract 6 | |
|---------------------------|--|
| Owner/Address: | Robert F. & Janet L. Cone |
| | 389 Lake Aires Rd. |
| | Fairmont, MN 56031 |
| | |
| Tract 7 | |
| Owner/Address: | Robert F. & Janet L. Cone |
| | 389 Lake Aires Rd. |
| | Fairmont, MN 56031 |
| | ······································ |
| Tract 8 | |
| Owner/Address: | Robert F. & Janet L. Cone |
| | 389 Lake Aires Rd. |
| | Fairmont, MN 56031 |
| [| |
| Tract 9* | |
| Owner/Address: | James & Ronda Cone Trust Agreement |
| | James & Ronda Cone, Trustees |
| | 640 W Interlaken Rd. |
| | Fairmont, MN 56031 |
| | |
| Tract 9 Owner/Address: | Robert F. & Janet L. Cone |
| Owner/Address: | 389 Lake Aires Rd. |
| | Fairmont, MN 56031 |
| | |
| Tract 10* | |
| Owner/Address: | James & Ronda Cone Trust Agreement |
| Owner/Address. | James & Ronda Cone, Trustees |
| | 640 W Interlaken Rd. |
| | Fairmont, MN 56031 |
| | |
| Tract 11* | |
| Owner/Address: | Robert F. & Janet L. Cone |
| | 389 Lake Aires Rd. |
| | Fairmont, MN 56031 |
| | |
| Tract 12* | |
| Owner/Address: | Merwin Thompson Farms, Inc. |
| | c/o Roger Thompson |
| | 190 280th Ave. |
| | Elmore, MN 56027 |
| | |

۰.

| Tract 13* | |
|----------------|-------------------------------------|
| Owner/Address: | Todd & Malorie Thompson |
| | 268 280th Ave. |
| | Elmore, MN 56027 |
| Tract 14* | |
| Owner/Address: | Todd & Malorie Thompson |
| Owner/Address. | 268 280th Ave. |
| | |
| | Elmore, MN 56027 |
| Tract 15* | |
| Owner/Address: | Roger Thompson & |
| | Donna Bosek Revocable Trust, et al. |
| | 10695 Kingsfield Lane |
| | Woodbury, MN 55139 |
| | |
| Tract 16 | |
| Owner/Address: | Roger Thompson & |
| | Donna Bosek Revocable Trust, et al. |
| | 10695 Kingsfield Lane |
| | Woodbury, MN 55139 |
| Tract 17* | ······ |
| Owner/Address: | Merwin E. Thompson Farms, Inc. & |
| Owner/Address. | Roger C. Thompson, et al. |
| | 190 280th Ave. |
| | Elmore, MN 56027 |
| L | Elmore, Mix 30027 |
| Tract 18* | |
| Owner/Address: | Merwin E. Thompson Farms, Inc. & |
| | Roger C. Thompson, et al. |
| | 190 280th Ave. |
| | Elmore, MN 56027 |
| | |
| Tract 19* | Manuin Thomson Forms Inc. |
| Owner/Address: | Merwin Thompson Farms, Inc. |
| | c/o Roger Thompson |
| | 190 280th Ave. |
| | Elmore, MN 56027 |

۲.

WHEREAS, this Petition is signed by at least 26% of the owners of the property area affected by the proposed improvement project; and WHEREAS, this Petition is signed by: (1) at least 26% of the owners of the property affected by the proposed improvements; (2) at least 26% of the owners of the property that the proposed improvement passes over; (3) the owners of at least 26% of the property area affected by the proposed improvement; or (4) the owners of at least 26% of the property area that the proposed improvement passes over; and

WHEREAS. Petitioner provides herewith a surety bond in the face amount of \$50,000 payable to the Drainage Authority of Faribault-Martin County Judicial Ditch No. 414, said bond conditioned to pay the costs incurred if the proceeding are dismissed or a contract is not awarded to allow the costs incurred to exceed the amount of the bond and that they will cause additional bond to be filed if it appears that the costs exceed the amount of the bond; and

WHEREAS, Petitioner has been informed and understands that they may not withdraw as a Petitioner at any time after this Petition is accepted by the Drainage Authority. Petitioner further acknowledges that if the proposed drainage project is not constructed, they are liable to the Drainage Authority for all of the costs incurred including engineering, legal and miscellaneous fees and expenses in relation to this Petition as outlined under Minnesota Statutes 103E; and

WHEREAS, this Petition may be signed in counterparts.

NOW THEREFORE, Petitioners request the Faribault County Auditor present this Petition to the Faribault County Board of Commissioners (after examination by legal counsel), and for the formation and appointment of members of the Faribault and Martin County Joint County Board of Commissioners, to act together as the drainage authority to oversee the proposed Improvement Project proceeding, and, after formation, further request the acceptance of the Petition and for the appointment of Chuck Brandel. I+S Group, or, in the alternative, another engineer skilled in public drainage matters, to examine the proposed work.

| Owner Signature | Property Owned | Affected Acres |
|----------------------|------------------------|----------------|
| Robert F. Cone | Parcel ID: 14.019.0100 | 33.50 |
| Robert F. Cone | Parcel ID: 03.024.0200 | 9.22 |
| <u>Janet J. Cone</u> | Parcel ID: 03.024.0600 | 39.13 |


- 5 -

| Ow | ner Signature | Property Owned | Affected Acres |
|---------------------------|--|------------------------|----------------|
| James & Rond | es & Ronda Cone la Cone Trust Agreement es & Ronda Cone la Cone Trust Agreement | Parcel ID: 14.010.0400 | 151.74 |
| | Id Thompson hompson Farms, Inc P. D. A | Parcel ID: 14.030.0100 | 36.56 |
| Todd Thomp Malorie Tho | u Ethrapp | Parcel ID: 14.030.0600 | 80.93 |

 \overline{v}

Bruce E. Sellers Attorney for Petitioners Wendland Sellers Law Office 825 East Second Street P.O. Box 247 Blue Earth, MN 56013 507-526-2196

This petition is prepared by: Bruce E. Sellers, Attorney at Law Wendland Sellers Bromeland, P.A. 825 East Second Street, P.O. Box 247 Blue Earth, MN 56013 507-526-2196





e' . ' '

Bond No. 66329842

SURETY BOND Public Official, License or Permit Bonds and Probate Bonds

SURETY BOND

KNOW ALL MEN BY THESE PRESENTS

| That we,Todd Thompson and Faribault-Martin County Judicial Ditch 414 landowners/petitioners, as Principal, and the |
|--|
| Auto-Owners Insurance Company, a corporation organized under the laws of the State of |
| Michigan, and having its principal office at Lansing, Michigan, as Surety, are held and firmly bound unto |
| Drainage Authority for Faribault-Martin County J.D. 414 in the penal sum of (\$ 50.000.00) |
| Fifty Thousand and 00/100 Dollars, |
| lawful money of the United States of America, for which payment, well and truly to be made, we jointly and severally bind ourselves, our successors, administrators and assigns, firmly by these presents. |
| SIGNED, SEALED, and DATED this day of day of,,, |
| WHEREAS the aforesaid Principal has |
| of Faribault-Martin County Judicial Ditch 414. Said petition is being addressed before the Board of Commissioners Drainage Author |
| (If a License or Permit Bond insert "been granted a license or permit as (name business) by the said Obligee for the period of one year from (date)") of Faribault-Martin County pursuant to Minnesota Statutes 103E.215 with respect to a petition for improvement. (#1) |
| (If a Probate Bond insert "been appointed [Executor, Administrator, Guardian, Conservator] of the estate of [name of deceased, minor or incompetent]") |
| NOW, THEREFORE, THE CONDITION OF THIS OBLIGATION IS SUCH, that if the aforesaid Principal shall |
| pay all cost and expenses which may be incurred in case the proceedings herein are dismissed for any reason and no contract is (If a Public Official Bond insert "faithfully perform the duties of said office") |
| entered into for the construction of such improvement as proposed in the petition. Petitioners covenant they will not allow the costs (If a License or Permit Bond insert "comply with the laws of the aforesaid Obligee governing said License or Permit") |
| incurred to exceed the amount of the bond submitted herewith. Being part of a County Ditch the improvement will be a public (#2) Principal as (Guardian, Administrator, Conservator, Executor, etc.) will faithfully discharge the duties of their trust as Fiduciary of the person and/or estate in this matter according to law. |
| Then this obligation shall be void, otherwise to remain in full force and effect. |
| PROVIDED: That the liability of the Surety shall in no event exceed the penalty of this Bond. |
| the petitioners acknowledge that they have been informed and understand that they may not withdraw as a petitioner at any time (If no further conditions insert "no further conditions") |
| once this petition is filed. The petitioners understand that if the proposed drainage proceedings are dismissed each of them is |
| responsible for the payment of all costs incurred. The Surety may terminate this bond at any time by giving thirty (30) days written |
| notice of cancellation to both the Obligee and the Principal. |
| Todd Thompson and Faribault-Martin County Judicial Ditch 414 landowners/petitione |
| Principal Auto-Owners |
| BySurety |
| Attorney-in-Fact |
| 50 ONINERS MSUR |

BOND NUMBER_

• · · ·

Todd Thompson and Faribault-Martin County Judicial Ditch 414

#1 This bond may be automatically renewed for additional terms by Continuation Certificate issued by the Surety.

#2 utility. If a contract is entered into for the construction of such improvement the petitioners acknowledge that they have been informed and understand that they may not withdraw as petitioner at any time once this petition is filed. The petitioners understand that if the proposed drainage proceedings are dismissed each of them is responsible for the payments of all costs incurred. The Surety may terminate this bond at any time by giving thirty (30) as written notice of cancellation to both the Obligee and the Principal.

DATE AND ATTACH TO ORIGINAL BOND

AUTO-OWNERS INSURANCE COMPANY

LANSING, MICHIGAN

POWER OF ATTORNEY

NO. 66329842

KNOW ALL MEN BY THESE PRESENTS: That the AUTO-OWNERS INSURANCE COMPANY AT LANSING, MICHIGAN, a Michigan Corporation, having its principal office at Lansing, County of Eaton, State of Michigan, adopted the following Resolution by the directors of the Company on January 27, 1971, to wit:

"RESOLVED, That the President or any Vice President or Secretary or Assistant Secretary of the Company shall have the power and authority to appoint Attorneys-in-fact, and to authorize them to execute on behalf of the Company, and attach the seal of the Company thereto, bonds and undertakings, recognizances, contracts of indemnity, and other writings obligatory in the nature thereof. Signatures of officers and seal of Company imprinted on such powers of attorney by facsimite shall have same force and effect as if manually affixed. Said officers may at any time remove and revoke the authority of any such appointee."

Does hereby constitute and appoint CHAD W OSTERMANN

its true and lawful attomey(s)-in-fact, to execute, seal and deliver for and on its behalf as surety, any and all bonds and undertakings, recognizances, contracts of indemnity and other writings obligatory in the nature thereof, and the execution of such instrument(s) shall be as binding upon the AUTO-OWNERS INSURANCE COMPANY AT LANSING, MICHIGAN as fully and amply, to all intents and purposes, as if the same had been duly executed and acknowledged by its regularly elected officers at its principal office.

IN WITNESS WHEREOF, the AUTO-OWNERS INSURANCE COMPANY AT LANSING, MICHIGAN, has caused this to be signed by its authorized officer this 1st day of August, 2016.

Denise Williams

Denise Williams

Senior Vice President

STATE OF MICHIGAN SS.

On this 1st day of August, 2016, before me personally came Denise Williams, to me known, who being duly sworn, did depose and say that they are Denise Williams, Senior Vice President of AUTO-OWNERS INSURANCE COMPANY, the corporation described in and which executed the above instrument, that they know the seal of said corporation, that the seal affixed to said instrument is such Corporate Seal, and that they received said instrument on behalf of the corporation by authority of their office pursuant to a Resolution of the Board of Directors of said corporation.

My commission expires _____ March 10, 2022

Thusen Susan E. Theisen

2019

Notary Public

STATE OF MICHIGAN SS.

I, the undersigned First Vice President, Secretary and General Counsel of AUTO-OWNERS INSURANCE COMPANY, do hereby certify that the authority to issue a power of attorney as outlined in the above board of directors resolution remains in full force and effect as written and has not been revoked and the resolution as set forth is now in force.

Signed and sealed at Lansing, Michigan. Dated this _____1st ____ day of _____July

INERS INS CORPORATE SËA NG MI

William F. Woodbury, First Vice President, Secretary and General Counsel

WooNyr

Auto-Owners Insurance

· • •

.

LIFE - HOME - CAR - BUSINESS

EXECUTION REPORT (Detach and return with a copy of original bond.) NO. <u>66329842</u>

| Agency Name M & M INSURANCE AGENCY LLC | Agency Code 06-0636-00 |
|--|-----------------------------|
| Name of Principal TODD THOMPSON AND FARIBAULT-MARTIN COUNTY JUDICIAL DIT | Effective Date 07/01/2019 |
| Mailing Address 268 280TH AVE, ELMORE, MN 56027-504 | Premium Charge \$1.080.00 |
| Name of Obligee DRAINAGE AUTHORITY FOR FARIBAULT-MARTIN COUNTY JUDICIA | Amount of Bond \$50,000.00 |
| Address of Obligee PO BOX 130, BLUE EARTH, MN 56013-0130 | Type of Bond License/Permit |
| | |

COMPLETE AND ATTACH ALL PAPERS UNDER THIS REPORT THE SAME DAY THE BOND IS SIGNED

| PIN | TRACT NO. | OWNER | Affected Property Owners | Affected Property Owners Received | Passed Over Property Owners | Passed Over Property Owners Received | Total Affected Property Area | Affected Property Area Received | Total Passed Over Property Area | Passed Over Property Area Received |
|-------------|--------------|--|--------------------------------|--|--------------------------------------|--|---------------------------------------|--|---|--|
| 14.019.0300 | 1 | TERRY L & SONIA PETERSON | 1 | | 1 | | 24.67 | | 24.67 | 0.00 |
| 14.019.0300 | 2 | TERRY L & SONJA PETERSON | | | | | 5.35 | | | |
| 14.019.0100 | 3 | ROBERT F & JANET L CONE | 1 | 1 | | | 8.92 | | | |
| 14.019.0400 | 4 | JAMES & RONDA CONE TRUST AGREEMENT | 1 | 1 | 1 | 1 | 32.19 | 32.19 | 32.19 | 32.19 |
| 14.019.0100 | 5 | ROBERT F & JANET L CONE | | | | | 1.89 | 1.89 | | |
| 14.019.0400 | 5 | JAMES & RONDA CONE TRUST AGREEMENT | | | | | 38.65 | 38.65 | 38.65 | 38.65 |
| 03.024.0200 | 6 | ROBERT F & JANET L CONE | | | | | 9.22 | 9.22 | | |
| 03.024.0600 | 7 | ROBERT F & JANET L CONE | | | | | 5.46 | 5.46 | | |
| 03.024.0600 | 8 | ROBERT F & JANET L CONE | | | | | 33.67 | 33.67 | | |
| 14.019.0100 | 9 | ROBERT F & JANET L CONE | | | | | 2.69 | 2.69 | | |
| 14.019.0400 | 9 | IAMES & RONDA CONE TRUST AGREEMENT | | | | | 41.07 | 41.07 | 41.07 | 41.07 |
| 14 019 0400 | 10 | JAMES & RONDA CONE TRUST AGREEMENT | | | | | 39.83 | 39.83 | 39.83 | 39.83 |
| 14.019.0100 | 11 | ROBERT F & JANET L CONE | | | 1 | 1 | 20.00 | 20.00 | 20.00 | 20.00 |
| 14 030 0100 | 12 | MERWIN THOMPSON FARMS INC | 1 | 1 | 1 | 1 | 21.19 | 21.19 | 21.19 | 21.19 |
| 14.030.0600 | 13 | TODD & MALORIE THOMPSON | 1 | 1 | 1 | 1 | 38.70 | 38.70 | 38.70 | 38.70 |
| 14.030.0600 | 14 | TODD & MALORIE THOMPSON | | | | | 42.23 | 42.23 | 42.23 | 42.23 |
| 03 025 0100 | 15 | ROGER THOMPSON & DONNA BOSEK REVOCABLE TRUST ET AL | 1 | | 1 | | 28.55 | | 28.55 | 0.00 |
| 03 025 0100 | 16 | ROGER THOMPSON & DONNA BOSEK REVOCABLE TRUST ET AL | | | | | 3.75 | | | |
| 14 030 1200 | 17 | MERWIN E THOMPSON FARMS INC & ROGER C THOMPSON ET AL | 1 | | 1 | | 10.89 | | 10.89 | 0.00 |
| 14.030.1200 | 18 | MERWIN E THOMPSON FARMS INC & ROGER C THOMPSON ET AL | | | | | 20.91 | | 20.91 | 0.00 |
| 14.030.0100 | 19 | MERWIN THOMPSON FARMS INC | | | | | 15.37 | 15.37 | | 15.37 |
| | | | 7 | 4 | 7 | 4 | 445.19 | 342.14 | 374.25 | 289.23 |
| | | | | 57.14% | | 57.14% | | 76.85% | | 77.28% |

Parcels, Tracts, and Owners considered "passed over" are marked in red

BEFORE THE JOINT BOARD OF MARTIN & FARIBAULTCOUNTY COMMISSIONERS, ACTING AS DRAINAGE AUTHORITY FOR MARTIN & FARIBAULT COUNTY JD #414

Findings of Fact and Order Regarding Acceptance of Petition and Appointment of Engineer

WHEREAS, a Petition was submitted to the Joint Board of Martin & Faribault County Board of Commissioners, acting as Drainage Authority for Martin & Faribault County JD #414, requesting the Improvement of Branch A40 of Martin & Faribault County JD #414; and

WHEREAS, the Petition was referred to Kurt Deter to review to establish that it meets the requirements of the a Petition, under Minnesota Statutes 103E.215; and

WHEREAS, the Petition does meet the requirements under Minnesota Statutes 103E.215.

NOW, THEREFORE, the Joint Board of Martin & Faribault County Board of Commissioners, acting as Drainage Authority for Martin & Faribault County JD #414, makes the following Findings of Fact and Order:

FINDINGS OF FACT

1. That the Petition is accepted as meeting the requirements of Minnesota Statutes 103E.215.

2. That I&S Group has been recommended to be the engineers for the proposed Improvement project.

ORDER


NOW, THEREFORE, it is hereby ordered that the Petition is accepted for the Improvement of Branch A40 of Martin & Faribault County JD #414 and I&S Group is appointed the engineer and is to proceed in the preparation of a Preliminary Engineer's Report.


Dated this 17th day of September, 2019.


JOINT BOARD OF **MARTIN & FARIBAULTCOUNTY COMMISSIONERS, ACTING AS DRAINAGE AUTHORITY** FOR MARTIN & FARIBAULT COUNTY JD #414


By <u>Elliot</u> Belgard Its Chairperson

Appendix C: Maps









ISG Soil

Classification Мар


Judical Ditch No. 414 Martin - Faribault County, Minnesota Tuesday, January 7, 2020

PN: 19-23608


Source: Orthophotograph (MnGeo WMS, 2015) Tile/Ditch (XX County, 12/16/2016) Parcels (XX County, 12/16/2016) Lakes (MN DNR, July, 2008) Major Stream (MN DNR, July 2008) Counties (MN DNR, July 2013) PLSS (MnGeo/USGS)





1 inch = 833 feet





Iowa











Appendix D: Multipurpose Drainage Management Plan

Multi-Purpose Drainage Management Plan

Multi-purpose drainage management incorporates Best Management Practices (BMPs) which utilize effective measures aimed at reducing sediment and nutrient loading, and improving water quality. These BMPs are divided into the following three areas.

Preventative Measures

Preventative measures that can be applied throughout the watershed include crop rotation, cover crops, residue management, and nutrient management. These measures are aimed at controlling sediment, minimizing erosion and nutrient loss, and sustaining the soils health, all without dramatically changing the current land use of the landscape.

Control Measures

Control measures are practices aimed at improving water quality directly associated with the flow of water by reducing peak flow and providing in-stream storage, sedimentation, and nutrient uptake. Examples of control measures include alternative tile intakes, grassed waterways, two stage ditches, water control structures, and controlled subsurface drainage. These practices are directly linked to the conveyance of subsurface tile water or open channel ditch flow.

Treatment Measures

The function of treatment measures is to improve water quality by directly removing sediment and nutrients from the subsurface or surface water flow throughout a watershed. Examples of treatment measures include surge basins (storage ponds), filter/buffer strips, wetland restorations, woodchip bioreactors, and water and sediment control basins (WASCOBs). These practices may be incorporated to either the public or private drainage systems.

Conservative Drainage Practices

Conservative drainage practices, such as construction of controlled drainage systems, provide an option for improving the water quality within a drainage system. Through utilization of control structures, these systems are designed to allow agricultural producers to regulate water levels in their fields. The water level in the ground can be lowered during planting and harvest seasons and allowed to rise during the growing season. Water and nutrients stored in the soil during the growing season can then be used by the crops during drier periods, potentially increasing yields.

Funding

There are several outside sources of funding to potentially help pay for water quality improvements implemented in a ditch improvement project such as this. A main source of funding for this type of project is through the Minnesota Board of Water and Soil Resources (BWSR) Clean Water Fund (CWF). The primary purpose of activities funded with grants associated with the CWF is to restore, protect and enhance water quality. One CWF grant program is the Multipurpose Drainage Management Grant. This grant is geared towards implementing practices that will reduce the transport of sediment and nutrient loads. Some practices that have been funded in the past include grade stabilization, grassed waterways, water and sediment control basins, alternative side inlets, saturated buffers, storage wetlands, denitrifying bioreactors, etc.

Another potential source is the Legislative-Citizen Commission on Minnesota Resources (LCCMR) Environment and Natural Resources Trust Fund (ENRTF) which was established to provide funding for activities that protect, conserve, preserve, and enhance Minnesota's "air, water, land, fish, wildlife, and other natural resources." The LCCMR prioritizes innovative ideas that provide multiple benefits.


Potential locations for additional BMPs are shown on the Multi-Purpose Drainage Management map in this Appendix. If landowners are interested in pursuing practices that go beyond this project scope, a few programs may be a source for funding. The Agriculture Best Management Practices (BMP) Loan Program provides loans to rural landowners to encourage BMPs that help counteract pollution problems.

Another option for individual landowners that are interested in pursuing additional practices is the Environmental Quality Incentives Program (EQIP). EQUIP is a voluntary program through the NRCS that provides financial assistance to individual landowners for various conservative practices as identified above.

In addition, the BWSR Community Partners Grant may be an option. This grant leverages the interest of nongovernmental partners such as lake and river associations, boy/girl scout troops and other civic groups to install on-the ground projects that reduce runoff and keep water on the land. It also allows for multiple local government units to work together on a project that involves the Community Partners Grant. Projects installed with the Community Partners Grant are intended to be structural or vegetative practices designed to reduce runoff and/or keep water on the land.

All of the water quality measures proposed with this project are applicable for some source of outside funding. The sources listed above are grants that could be a good fit for this project and if the timing of the project works in conjunction with the grant schedule. These grants can be applied for, if there is support from the drainage authority and/or interest from landowners.

Currently, this project proposes to use Alternative Tile Inlets which we call Water Quality Inlets in all public road ditches. In addition, a 1-acre storage pond is recommended to be implemented as part of the improvement project. Potential locations for these and additional BMPs are shown on the *Multi-Purpose Drainage Management Map* and will be proposed to landowners. Furthermore; additional water quality measures can be implemented with this project if requested.



Appendix E: Modeling with Maps

G Architecture + Engineering + Environmental + Planning

MARTIN AND FARIBAULT COUNTIES JUDICIAL DITCH No. 414 January 28, 2020



Option 1 - No Storage

XP SWMM FLOWRATE TABLE

| | | | 2-yr | | | 5-yr | | | 10-yr | | | 25-yr | | | 50-yr | | 100-yr | | |
|-----------------------------------|------------|-------------------|-------------------|----------|-------------------|-------------------|----------|-------------------|-------------------|----------|-------------------|-------------------|----------|-------------------|-------------------|----------|-------------------|-------------------|----------|
| Location | Conveyence | Existing (cfs) | Proposed (cfs) | % Change |
| | Open Ditch | 260.00 | 287.80 | 11% | 528.00 | 543.67 | 3% | 760.00 | 768.90 | 1% | 1110.00 | 1114.31 | 0% | 1410.00 | 1426.55 | 1% | 1760.00 | 1783.54 | 1% |
| JD 414 Open Ditch - System Outlet | Overflow | 0.00 | 0.00 | N/A |
| | Total | 260.00 | 287.80 | 11% | 528.00 | 543.67 | 3% | 760.00 | 768.90 | 1% | 1110.00 | 1114.31 | 0% | 1410.00 | 1426.55 | 1% | 1760.00 | 1783.54 | 1% |
| JD 414 Open Ditch - Branch A40 | Open Ditch | 134.00 | 161.80 | 21% | 271.00 | 286.67 | 6% | 389.00 | 397.90 | 2% | 567.00 | 571.31 | 1% | 722.00 | 738.55 | 2% | 901.00 | 924.54 | 3% |
| Outlet | Overflow | 0.00 | 0.00 | N/A |
| outlet | Total | 134.00 | 161.80 | 21% | 271.00 | 286.67 | 6% | 389.00 | 397.90 | 2% | 567.00 | 571.31 | 1% | 722.00 | 738.55 | 2% | 901.00 | 924.54 | 3% |
| | Tile | 7.62 | 37.58 | 393% | 11.66 | 40.57 | 248% | 13.69 | 44.05 | 222% | 27.17 | 52.83 | 94% | 32.19 | 69.57 | 116% | 33.37 | 75.94 | 128% |
| Branch A40 Outlet | Overflow | 2.16 | 0.00 | -100% | 13.24 | 0.00 | -100% | 23.19 | 1.73 | -93% | 41.18 | 19.84 | -52% | 58.39 | 37.56 | -36% | 77.19 | 58.15 | -25% |
| | Total | 9.77 | 37.58 | 284% | 24.90 | 40.57 | 63% | 36.88 | 45.78 | 24% | 68.35 | 72.67 | 6% | 90.58 | 107.12 | 18% | 110.55 | 134.09 | 21% |
| | Tile | 1.26 | 8.79 | 599% | -0.93 | 8.80 | -1043% | -0.93 | 8.81 | -1053% | -0.87 | -3.68 | 325% | -0.87 | -3.41 | 294% | -0.86 | -3.14 | 264% |
| Branch A43 Outlet | Overflow | 4.03 | 5.84 | 45% | 6.42 | 9.43 | 47% | 8.90 | 13.05 | 47% | 12.83 | 18.56 | 45% | 16.27 | 23.74 | 46% | 19.77 | 28.61 | 45% |
| | Total | 5.29 | 14.63 | 177% | 5.49 | 18.23 | 232% | 7.98 | 21.87 | 174% | 11.96 | 14.88 | 24% | 15.40 | 20.33 | 32% | 18.91 | 25.47 | 35% |
| | Tile | 0.84 | 1.46 | 74% | 0.85 | 1.46 | 72% | 0.85 | 1.46 | 72% | 0.83 | 1.46 | 75% | 0.82 | 1.46 | 77% | 0.82 | 1.46 | 78% |
| Branch A45 Outlet | Overflow | 0.51 | 0.00 | -100% | 0.75 | 0.06 | -92% | 1.13 | 0.19 | -83% | 1.77 | 0.53 | -70% | 2.41 | 0.83 | -66% | 3.05 | 1.16 | -62% |
| | Total | 1.35 | 1.46 | 8% | 1.60 | 1.51 | -5% | 1.98 | 1.65 | -16% | 2.60 | 1.98 | -24% | 3.23 | 2.28 | -29% | 3.87 | 2.62 | -32% |
| | Tile | 0.62 | 4.04 | 550% | 0.63 | 3.21 | 412% | 0.63 | 3.28 | 420% | 0.63 | 3.31 | 426% | 0.63 | 3.30 | 422% | 0.63 | 3.30 | 422% |
| Branch A46 Outlet | Overflow | 0.63 | 5.29 | 743% | 0.81 | 8.90 | 994% | 1.02 | 10.79 | 959% | 1.04 | 12.64 | 1116% | 0.63 | 12.59 | 1897% | 0.56 | 12.39 | 2133% |
| | Total | 1.25 | 9.32 | 647% | 1.44 | 12.11 | 741% | 1.65 | 14.07 | 753% | 1.67 | 15.95 | 855% | 1.26 | 15.89 | 1158% | 1.19 | 15.69 | 1222% |
| | Tile | 0.27 | 0.66 | 143% | 0.28 | 0.69 | 151% | 0.28 | 0.69 | 147% | 0.28 | 0.69 | 147% | 0.28 | 0.69 | 145% | 0.28 | 0.69 | 146% |
| Branch A47 Outlet | Overflow | 0.20 | 1.11 | 457% | 0.30 | 1.51 | 406% | 0.35 | 1.87 | 427% | 0.39 | 2.42 | 520% | 0.40 | 2.49 | 515% | 0.40 | 2.40 | 494% |
| | Total | 0.47 | 1.77 | 275% | 0.57 | 2.20 | 284% | 0.63 | 2.56 | 303% | 0.67 | 3.10 | 365% | 0.68 | 3.17 | 364% | 0.68 | 3.09 | 351% |
| Denotes peak flows less than or | | | | | | | | | | | | | | | | | | | |

equal to existing

MARTIN AND FARIBAULT COUNTIES JUDICIAL DITCH No. 414 February 6, 2020



Option 1 - No Storage

XP SWMM ELEVATION TABLE

| | | 2-yr | | | 5-yr | | | 10-yr | | | 25-yr | | | 50-yr | | | 100-yr | |
|--|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|
| Location | Existing (MSL) | Proposed (MSL) | Difference |
| Branch A40 Outlet - JD 414 Open Ditch | 1117.70 | 1117.00 | -0.70 | 1118.37 | 1117.05 | -1.32 | 1118.67 | 1117.10 | -1.57 | 1120.39 | 1117.22 | -3.17 | 1120.95 | 1117.43 | -3.52 | 1121.08 | 1117.51 | -3.57 |
| Branch A41 Connection to Branch A40 | 1125.72 | 1125.64 | -0.08 | 1126.04 | 1125.78 | -0.26 | 1126.36 | 1125.97 | -0.39 | 1126.73 | 1126.39 | -0.34 | 1127.08 | 1126.70 | -0.38 | 1127.54 | 1127.03 | -0.51 |
| North CSAH 2 | 1127.94 | 1128.04 | 0.10 | 1128.45 | 1128.50 | 0.05 | 1128.88 | 1128.88 | 0.00 | 1129.49 | 1129.47 | -0.02 | 1129.97 | 1129.96 | -0.01 | 1130.33 | 1130.38 | 0.04 |
| South CSAH 2 | 1128.26 | 1128.09 | -0.17 | 1128.66 | 1128.52 | -0.15 | 1129.01 | 1128.88 | -0.13 | 1129.59 | 1129.47 | -0.12 | 1130.07 | 1129.96 | -0.11 | 1130.56 | 1130.39 | -0.17 |
| West 310th Street | 1140.19 | 1140.15 | -0.04 | 1140.34 | 1140.33 | -0.01 | 1140.44 | 1140.43 | -0.01 | 1140.56 | 1140.56 | 0.00 | 1140.65 | 1140.64 | 0.00 | 1140.73 | 1140.73 | 0.00 |
| Branch A47 Connection to Branch A46 | 1128.52 | 1128.18 | -0.34 | 1128.66 | 1128.52 | -0.15 | 1129.01 | 1128.88 | -0.13 | 1129.59 | 1129.47 | -0.12 | 1130.07 | 1129.96 | -0.11 | 1130.56 | 1130.39 | -0.17 |
| Denotes peak elevation less than | | | | | | | | | | | | | | | | | | |

or equal to existing

MARTIN AND FARIBAULT COUNTIES JUDICIAL DITCH No. 414 January 28, 2020



Option 2 - 1ac Storage Pond

XP SWMM FLOWRATE TABLE

| en Ditch 2 verflow Total 2 en Ditch 1 verflow | (cfs) 260.00 0.00 260.00 134.00 | Proposed (cfs) 268.08 0.00 268.08 142.08 | % Change 3% N/A 3% | (cfs) 528.00 0.00 | Proposed (cfs) 525.68 0.00 | % Change 0% | Existing (cfs) 760.00 | Proposed (cfs) 756.22 | % Change 0% | (cfs) | Proposed (cfs) | % Change | Existing (cfs) | Proposed (cfs) | % Change | Existing (cfs) | Proposed (cfs) | % Change |
|---|---|---|---|--|--|--|--|---|---|--|---|--|--|---|--|--|--|--|
| verflow Total 2 en Ditch 1 verflow | 0.00 260.00 134.00 | 0.00 268.08 | N/A | 0.00 | | | 760.00 | 756.22 | 00/ | 4440.00 | | | | | | | | |
| Total 2 en Ditch 1 verflow | 260.00 134.00 | 268.08 | , | | 0.00 | | | | 0% | 1110.00 | 1085.80 | -2% | 1410.00 | 1375.28 | -2% | 1760.00 | 1765.33 | 0% |
| en Ditch 1 verflow | 134.00 | | 3% | | | N/A | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A |
| verflow | | 142 08 | | 528.00 | 525.68 | 0% | 760.00 | 756.22 | 0% | 1110.00 | 1085.80 | -2% | 1410.00 | 1375.28 | -2% | 1760.00 | 1765.33 | 0% |
| | | 142.00 | 6% | 271.00 | 268.68 | -1% | 389.00 | 385.22 | -1% | 567.00 | 542.80 | -4% | 722.00 | 687.28 | -5% | 901.00 | 906.33 | 1% |
| | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A |
| | | 142.08 | 6% | 271.00 | 268.68 | -1% | 389.00 | 385.22 | -1% | 567.00 | 542.80 | -4% | 722.00 | 687.28 | -5% | 901.00 | 906.33 | 1% |
| Tile | 7.62 | 17.86 | 134% | 11.66 | 22.49 | 93% | 13.69 | 28.70 | 110% | 27.17 | 31.33 | 15% | 32.19 | 37.08 | 15% | 33.37 | 55.24 | 66% |
| verflow | 2.16 | 0.00 | -100% | 13.24 | 0.08 | -99% | 23.19 | 4.39 | -81% | 41.18 | 12.83 | -69% | 58.39 | 18.77 | -68% | 77.19 | 60.64 | -21% |
| Total | 9.77 | 17.86 | 83% | 24.90 | 22.57 | -9% | 36.88 | 33.09 | -10% | 68.35 | 44.15 | -35% | 90.58 | 55.85 | -38% | 110.55 | 115.88 | 5% |
| Tile | 1.26 | 8.48 | 574% | -0.93 | 8.45 | -1005% | -0.93 | 8.44 | -1013% | -0.87 | -3.60 | 316% | -0.87 | -3.30 | 281% | -0.86 | -3.07 | 256% |
| verflow | 4.03 | 5.78 | 44% | 6.42 | 9.36 | 46% | 8.90 | 13.33 | 50% | 12.83 | 18.48 | 44% | 16.27 | 23.54 | 45% | 19.77 | 28.39 | 44% |
| Total | 5.29 | 14.26 | 170% | 5.49 | 17.80 | 224% | 7.98 | 21.77 | 173% | 11.96 | 14.89 | 24% | 15.40 | 20.24 | 31% | 18.91 | 25.32 | 34% |
| Tile | 0.84 | 1.44 | 72% | 0.85 | 1.44 | 70% | 0.85 | 1.44 | 70% | 0.83 | 1.44 | 73% | 0.82 | 1.44 | 75% | 0.82 | 1.45 | 77% |
| verflow | 0.51 | 0.00 | -100% | 0.75 | 0.06 | -92% | 1.13 | 0.20 | -83% | 1.77 | 0.53 | -70% | 2.41 | 0.83 | -66% | 3.05 | 1.18 | -62% |
| Total | 1.35 | 1.44 | 7% | 1.60 | 1.50 | -6% | 1.98 | 1.64 | -17% | 2.60 | 1.97 | -24% | 3.23 | 2.27 | -30% | 3.87 | 2.62 | -32% |
| Tile | 0.62 | 4.05 | 552% | 0.63 | 3.09 | 393% | 0.63 | 2.83 | 350% | 0.63 | 2.82 | 347% | 0.63 | 2.86 | 352% | 0.63 | 2.90 | 359% |
| verflow | 0.63 | 5.27 | 739% | 0.81 | 8.76 | 977% | 1.02 | 10.53 | 934% | 1.04 | 12.30 | 1083% | 0.63 | 12.21 | 1836% | 0.56 | 12.06 | 2072% |
| Total | 1.25 | 9.31 | 646% | 1.44 | 11.85 | 723% | 1.65 | 13.36 | 711% | 1.67 | 15.11 | 805% | 1.26 | 15.06 | 1092% | 1.19 | 14.95 | 1160% |
| - | 0.27 | 0.67 | 144% | 0.28 | 0.68 | 147% | 0.28 | 0.68 | 143% | 0.28 | 0.68 | 144% | 0.28 | 0.68 | 143% | 0.28 | 0.68 | 143% |
| | 0.20 | 1.10 | 456% | 0.30 | 1.51 | 404% | 0.35 | 1.86 | 425% | 0.39 | 2.41 | 518% | 0.40 | 2.47 | 510% | 0.40 | 2.38 | 489% |
| Total | 0.47 | 1.77 | 275% | 0.57 | 2.19 | 281% | 0.63 | 2.54 | 301% | 0.67 | 3.09 | 362% | 0.68 | 3.14 | 360% | 0.68 | 3.06 | 347% |
| Ti /ei To Ti /ei To Ti /ei To | ile file file file file file file file f | ile 7.62 rflow 2.16 trail 9.77 ile 1.26 rflow 4.03 trail 5.29 ile 0.84 rflow 0.51 trail 1.35 ile 0.62 rflow 0.63 trail 1.25 ile 0.27 rflow 0.20 | ile 7.62 17.86 rflow 2.16 0.00 ptal 9.77 17.86 ile 1.26 8.48 rflow 4.03 5.78 ptal 5.29 14.26 ile 0.84 1.44 rflow 0.51 0.00 ptal 1.35 1.44 rile 0.62 4.05 rflow 0.63 5.27 ptal 1.25 9.31 ile 0.27 0.67 rflow 0.20 1.10 | ile 7.62 17.86 134% rflow 2.16 0.00 -100% ptal 9.77 17.86 83% ile 1.26 8.48 574% iflow 4.03 5.78 44% ptal 5.29 14.26 170% ile 0.84 1.44 72% rflow 0.51 0.00 -100% ptal 1.35 1.44 7% ile 0.62 4.05 552% rflow 0.63 5.27 739% ptal 1.25 9.31 646% ile 0.27 0.67 144% | Tile 7.62 17.86 134% 11.66 rflow 2.16 0.00 -100% 13.24 trail 9.77 17.86 83% 24.90 tile 1.26 8.48 574% -0.93 rflow 4.03 5.78 44% 6.42 trail 5.29 14.26 170% 5.49 tile 0.84 1.44 72% 0.85 rflow 0.51 0.00 -100% 0.75 ttal 1.35 1.44 7% 1.60 tile 0.62 4.05 552% 0.63 rflow 0.63 5.27 739% 0.81 trail 1.25 9.31 646% 1.44 tile 0.27 0.67 144% 0.28 traile 0.20 1.10 456% 0.30 | Tile 7.62 17.86 134% 11.66 22.49 rflow 2.16 0.00 -100% 13.24 0.08 tal 9.77 17.86 83% 24.90 22.57 tile 1.26 8.48 574% -0.93 8.45 rflow 4.03 5.78 44% 6.42 9.36 tal 5.29 14.26 170% 5.49 17.80 tile 0.84 1.44 72% 0.85 1.44 rflow 0.51 0.00 -100% 0.75 0.06 tal 1.35 1.44 7% 1.60 1.50 tile 0.62 4.05 552% 0.63 3.09 rflow 0.63 5.27 739% 0.81 8.76 tal 1.25 9.31 646% 1.44 11.85 tal 0.27 0.67 144% 0.28 0.68 tal 0.27 0.67 | Tile 7.62 17.86 134% 11.66 22.49 93% rflow 2.16 0.00 -100% 13.24 0.08 -99% trlow 2.16 0.00 -100% 13.24 0.08 -99% trlow 2.16 0.00 -100% 13.24 0.08 -99% trlow 1.26 8.48 574% -0.93 8.45 -1005% rflow 4.03 5.78 44% 6.42 9.36 46% trla 5.29 14.26 170% 5.49 17.80 224% trle 0.84 1.44 72% 0.85 1.44 70% trlaw 0.51 0.00 -100% 0.75 0.06 -92% trla 1.35 1.44 7% 1.60 1.50 -6% trlaw 0.62 4.05 552% 0.63 3.09 393% trlaw 0.63 5.27 739% 0.81 | The image of the image. Image of the image | The image is a straight of the image is a straight | Tile7.6217.86134%11.6622.4993%13.6928.70110%rflow2.160.00 -100% 13.240.08 -99% 23.194.39 -81% trl9.7717.8683%24.9022.57 -9% 36.8833.09 -10% tile1.268.48574% -0.93 8.45 -1005% -0.93 8.44 -1013% tflow4.035.7844%6.429.3646%8.9013.3350%trla5.2914.26170%5.4917.80224%7.9821.77173%tile0.841.4472%0.851.4470%0.851.4470%trla0.510.00 -100% 0.750.06 -92% 1.130.20 -83% trla1.351.447%1.601.50 -6% 1.981.64 -17% tile0.624.05552%0.633.09393%0.632.83350%trla1.259.31646%1.4411.85723%1.6513.36711%tile0.270.67144%0.280.68147%0.280.68143%trla0.201.10456%0.301.51404%0.351.86425% | Tile7.6217.86134%11.6622.4993%13.6928.70110%27.17rflow2.160.00-100%13.240.08-99%23.194.39-81%41.18btal9.7717.8683%24.9022.57-9%36.8833.09-10%68.35ile1.268.48574%-0.938.45-1005%-0.938.44-1013%-0.87rflow4.035.7844%6.429.3646%8.9013.3350%12.83otal5.2914.26170%5.4917.80224%7.9821.77173%11.96tile0.841.4472%0.851.4470%0.851.4470%0.83rflow0.510.00-100%0.750.06-92%1.130.20-83%1.77otal1.351.447%1.601.50-6%1.981.64-17%2.60ile0.624.05552%0.633.09393%0.632.83350%0.63rflow0.635.27739%0.818.76977%1.0210.53934%1.04otal1.259.31646%1.4411.85723%1.6513.36711%1.67tile0.270.67144%0.280.68147%0.280.68143%0.28otal1.259.31 | Tile7.6217.86134%11.6622.4993%13.6928.70110%27.1731.33rflow2.160.00 -100% 13.240.08 -99% 23.194.39 -81% 41.1812.83trla9.7717.8683%24.9022.57 -9% 36.8833.09 -10% 68.3544.15tile1.268.48574% -0.93 8.45 -1005% 0.93 8.44 -1013% -0.87 -3.60 trlow4.035.7844%6.429.3646%8.9013.3350%12.8318.48total5.2914.26170%5.4917.80224%7.9821.77173%11.9614.89tile0.841.4472%0.851.4470%0.851.4470%0.831.44trlow0.510.00 -100% 0.750.06 -92% 1.130.20 -83% 1.770.53total1.351.447%1.601.50 -6% 1.981.64 -17% 2.601.97tile0.624.05552%0.633.09393%0.632.83350%0.632.82trlow0.635.27739%0.818.76977%1.0210.53934%1.0412.30total1.259.31646%1.4411.85723%1.6513.36711%1.6715.11 | Tile 7.62 17.86 134% 11.66 22.49 93% 13.69 28.70 110% 27.17 31.33 15% rflow 2.16 0.00 -100% 13.24 0.08 -99% 23.19 4.39 -81% 41.18 12.83 -69% trl 9.77 17.86 83% 24.90 22.57 -9% 36.88 33.09 -10% 68.35 44.15 -35% trl 1.26 8.48 574% -0.93 8.45 -1005% -0.93 8.44 -1013% 0.87 -3.60 316% trl 4.03 5.78 44% 6.42 9.36 46% 8.90 13.33 50% 12.83 18.48 44% trl 5.29 14.26 170% 5.49 17.80 224% 7.98 1.144 70% 1.89 24% trl 0.84 1.44 72% 0.85 1.44 70% 0.83 1.44 73% trl 0.51 0.00 -100% 0.75 0.06 -92% 1.13 0.20 -83% 1.77 0.53 -70% trl 0.51 0.00 -100% 0.75 0.06 -92% 1.13 0.20 -83% 1.77 0.53 -70% trl 0.51 0.00 -100% 0.75 0.66 1.98 1.64 -17% 2.60 1.97 -24% trl 0.52 4.05 552% 0.63 < | Tile 7.62 17.86 134% 11.66 22.49 93% 13.69 28.70 110% 27.17 31.33 15% 32.19 rflow 2.16 0.00 -100% 13.24 0.08 -99% 23.19 4.39 -81% 41.18 12.83 -69% 58.39 tal 9.77 17.86 83% 24.90 22.57 -9% 36.88 33.09 -10% 68.35 44.15 -35% 90.58 tile 1.26 8.48 574% -0.93 8.45 -1005% 0.93 8.44 -1013% -0.87 -3.60 316% -0.87 rflow 4.03 5.78 44% 6.42 9.36 46% 8.90 13.33 50% 12.83 18.48 44% 16.27 tal 5.78 44% 6.42 9.36 46% 8.90 13.33 50% 12.83 18.48 44% 16.27 tal 5.29 14.26 170% 5.49 17.80 224% 7.98 21.77 173% 11.96 14.89 24% 15.40 tile 0.84 1.44 72% 0.85 1.44 70% 0.85 1.44 70% 0.83 1.44 73% 0.82 trile 0.62 4.05 55% 0.66 1.98 1.64 -17% 2.60 1.97 24% 3.23 trile 0.62 4.05 55% 0.63 3.09 393% </td <td>Tile$7.62$$17.86$$134\%$$11.66$$22.49$$93\%$$13.69$$28.70$$110\%$$27.17$$31.33$$15\%$$32.19$$37.08$rflow$2.16$$0.00$$-100\%$$13.24$$0.08$$-99\%$$23.19$$4.39$$-81\%$$41.18$$12.83$$-69\%$$58.39$$18.77$$trlot$$9.77$$17.86$$83\%$$24.90$$22.57$$-9\%$$36.88$$33.09$$-10\%$$68.35$$44.15$$-35\%$$90.58$$55.85$Tile$1.26$$8.48$$574\%$$0.93$$8.45$$-1005\%$$0.93$$8.44$$-1013\%$$-0.87$$-3.60$$316\%$$-0.87$$-3.30$rflow$4.03$$5.78$$44\%$$6.42$$9.36$$46\%$$8.90$$13.33$$50\%$$12.83$$18.48$$44\%$$16.27$$23.54$trlat$5.29$$14.26$$170\%$$5.49$$17.80$$224\%$$7.98$$21.77$$173\%$$11.96$$14.48$$24\%$$15.40$$20.24$trle$0.84$$1.44$$72\%$$0.85$$1.44$$70\%$$0.85$$1.44$$70\%$$0.83$$1.44$$73\%$$0.82$$1.44$trlow$0.51$$0.00$$-100\%$$0.75$$0.06$$-92\%$$1.13$$0.20$$-83\%$$1.77$$0.53$$-70\%$$2.41$$0.83$trlat$1.35$$1.44$$7\%$$1.60$$1.50$$-6\%$$1.98$$1.64$$1$</td> <td>Tile$7.62$$17.86$$134\%$$11.66$$22.49$$93\%$$13.69$$28.70$$110\%$$27.17$$31.33$$15\%$$32.19$$37.08$$15\%$rflow$2.16$$0.00$$-100\%$$13.24$$0.08$$-99\%$$23.19$$4.39$$-81\%$$41.18$$12.83$$-69\%$$58.39$$18.77$$-68\%$trla$9.77$$17.86$$83\%$$24.90$$22.57$$-9\%$$36.88$$33.09$$-10\%$$68.35$$44.15$$-35\%$$90.58$$55.85$$-38\%$trla$1.26$$8.48$$574\%$$-0.93$$8.45$$-1005\%$$0.93$$8.44$$-1013\%$$0.87$$-3.60$$316\%$$0.87$$23.54$$45\%$trlw$4.03$$5.78$$44\%$$6.42$$9.36$$46\%$$8.90$$13.33$$50\%$$12.83$$18.48$$44\%$$16.27$$23.54$$45\%$trla$5.29$$14.26$$170\%$$5.49$$17.80$$224\%$$7.98$$21.77$$173\%$$11.46$$14.89$$24\%$$15.40$$20.244$$31\%$trla$0.84$$1.44$$72\%$$0.85$$1.44$$70\%$$0.83$$1.44$$73\%$$0.82$$1.44$$75\%$trla$0.51$$0.00$$-100\%$$0.75$$0.06$$-92\%$$1.13$$0.20$$-83\%$$1.77$$0.53$$-70\%$$2.41$$0.83$$1.64$trla$1.35$$1.44$$7\%$$1.60$<</td> <td>Tile 7.62 17.86 13.4% 11.66 22.49 93% 13.69 28.70 110% 27.17 31.33 15% 32.19 37.08 15% 33.37 rflow 2.16 0.00 -100% 13.24 0.08 -99% 23.19 4.39 -81% 41.18 12.83 -69% 58.39 18.77 -68% 77.19 trl 1.26 8.48 574% -0.93 8.45 -100% 68.35 44.15 -35% 90.58 55.85 -38% 110.55 ile 1.26 8.48 574% -0.93 8.44 -1013% -0.87 -3.60 316% -0.87 -3.30 281% -0.86 rflow 4.03 5.78 44% 6.42 9.36 46% 8.90 13.33 50% 12.83 18.48 44% 16.27 23.54 45% 19.77 trl 0.84 1.44 72% 0.85 1.44 70% 0.83 1.44 73% 0.82 1.44 75% 0.82 rflow</td> <td>Tile 7.62 17.86 13.4% 11.66 22.49 93% 13.69 28.70 110% 27.17 31.33 15% 32.19 37.08 15% 33.37 55.24 rflow 2.16 0.00 -100% 13.24 0.08 -99% 23.19 4.39 -81% 41.18 12.83 -69% 58.39 18.77 -68% 77.19 60.64 that 9.77 17.86 83% 24.90 22.57 -9% 36.88 33.09 -10% 68.35 44.15 -35% 90.58 55.85 -38% 110.55 115.88 ille 1.26 8.48 574% -0.93 8.44 -1013% -0.87 -3.60 316% -0.87 -3.30 281% -0.86 -3.07 rflow 4.03 5.78 44% 6.42 9.36 46% 8.90 13.33 50% 12.83 18.48 44% 16.27 23.54 45% 19.77 28.39 that 5.29 14.26 170% 5.49 17.80 22.47</td> | Tile 7.62 17.86 134% 11.66 22.49 93% 13.69 28.70 110% 27.17 31.33 15% 32.19 37.08 rflow 2.16 0.00 -100% 13.24 0.08 -99% 23.19 4.39 -81% 41.18 12.83 -69% 58.39 18.77 $trlot$ 9.77 17.86 83% 24.90 22.57 -9% 36.88 33.09 -10% 68.35 44.15 -35% 90.58 55.85 Tile 1.26 8.48 574% 0.93 8.45 -1005% 0.93 8.44 -1013% -0.87 -3.60 316% -0.87 -3.30 rflow 4.03 5.78 44% 6.42 9.36 46% 8.90 13.33 50% 12.83 18.48 44% 16.27 23.54 trlat 5.29 14.26 170% 5.49 17.80 224% 7.98 21.77 173% 11.96 14.48 24% 15.40 20.24 trle 0.84 1.44 72% 0.85 1.44 70% 0.85 1.44 70% 0.83 1.44 73% 0.82 1.44 trlow 0.51 0.00 -100% 0.75 0.06 -92% 1.13 0.20 -83% 1.77 0.53 -70% 2.41 0.83 trlat 1.35 1.44 7% 1.60 1.50 -6% 1.98 1.64 1 | Tile 7.62 17.86 134% 11.66 22.49 93% 13.69 28.70 110% 27.17 31.33 15% 32.19 37.08 15% rflow 2.16 0.00 -100% 13.24 0.08 -99% 23.19 4.39 -81% 41.18 12.83 -69% 58.39 18.77 -68% trla 9.77 17.86 83% 24.90 22.57 -9% 36.88 33.09 -10% 68.35 44.15 -35% 90.58 55.85 -38% trla 1.26 8.48 574% -0.93 8.45 -1005% 0.93 8.44 -1013% 0.87 -3.60 316% 0.87 23.54 45% trlw 4.03 5.78 44% 6.42 9.36 46% 8.90 13.33 50% 12.83 18.48 44% 16.27 23.54 45% trla 5.29 14.26 170% 5.49 17.80 224% 7.98 21.77 173% 11.46 14.89 24% 15.40 20.244 31% trla 0.84 1.44 72% 0.85 1.44 70% 0.83 1.44 73% 0.82 1.44 75% trla 0.51 0.00 -100% 0.75 0.06 -92% 1.13 0.20 -83% 1.77 0.53 -70% 2.41 0.83 1.64 trla 1.35 1.44 7% 1.60 < | Tile 7.62 17.86 13.4% 11.66 22.49 93% 13.69 28.70 110% 27.17 31.33 15% 32.19 37.08 15% 33.37 rflow 2.16 0.00 -100% 13.24 0.08 -99% 23.19 4.39 -81% 41.18 12.83 -69% 58.39 18.77 -68% 77.19 trl 1.26 8.48 574% -0.93 8.45 -100% 68.35 44.15 -35% 90.58 55.85 -38% 110.55 ile 1.26 8.48 574% -0.93 8.44 -1013% -0.87 -3.60 316% -0.87 -3.30 281% -0.86 rflow 4.03 5.78 44% 6.42 9.36 46% 8.90 13.33 50% 12.83 18.48 44% 16.27 23.54 45% 19.77 trl 0.84 1.44 72% 0.85 1.44 70% 0.83 1.44 73% 0.82 1.44 75% 0.82 rflow | Tile 7.62 17.86 13.4% 11.66 22.49 93% 13.69 28.70 110% 27.17 31.33 15% 32.19 37.08 15% 33.37 55.24 rflow 2.16 0.00 -100% 13.24 0.08 -99% 23.19 4.39 -81% 41.18 12.83 -69% 58.39 18.77 -68% 77.19 60.64 that 9.77 17.86 83% 24.90 22.57 -9% 36.88 33.09 -10% 68.35 44.15 -35% 90.58 55.85 -38% 110.55 115.88 ille 1.26 8.48 574% -0.93 8.44 -1013% -0.87 -3.60 316% -0.87 -3.30 281% -0.86 -3.07 rflow 4.03 5.78 44% 6.42 9.36 46% 8.90 13.33 50% 12.83 18.48 44% 16.27 23.54 45% 19.77 28.39 that 5.29 14.26 170% 5.49 17.80 22.47 |

equal to existing

MARTIN AND FARIBAULT COUNTIES JUDICIAL DITCH No. 414 February 6, 2020



Option 2 - 1ac Storage Pond

XP SWMM ELEVATION TABLE

| | | 2-yr | | | 5-yr | | | 10-yr | | | 25-yr | | | 50-yr | | 100-yr | | |
|--|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|
| Location | Existing (MSL) | Proposed (MSL) | Difference |
| Branch A40 Outlet - JD 414 Open Ditch | 1117.70 | 1115.85 | -1.85 | 1118.37 | 1115.96 | -2.40 | 1118.67 | 1116.09 | -2.58 | 1120.39 | 1116.14 | -4.26 | 1120.95 | 1116.24 | -4.72 | 1121.08 | 1116.51 | -4.57 |
| Branch A41 Connection to Branch A40 | 1125.72 | 1125.77 | 0.04 | 1126.04 | 1125.87 | -0.17 | 1126.36 | 1126.10 | -0.26 | 1126.73 | 1126.71 | -0.02 | 1127.08 | 1127.11 | 0.04 | 1127.54 | 1127.30 | -0.24 |
| North CSAH 2 | 1127.94 | 1128.08 | 0.14 | 1128.45 | 1128.52 | 0.07 | 1128.88 | 1128.89 | 0.01 | 1129.49 | 1129.48 | -0.01 | 1129.97 | 1129.98 | 0.00 | 1130.33 | 1130.39 | 0.05 |
| South CSAH 2 | 1128.26 | 1128.11 | -0.16 | 1128.66 | 1128.53 | -0.13 | 1129.01 | 1128.89 | -0.12 | 1129.59 | 1129.49 | -0.10 | 1130.07 | 1129.98 | -0.09 | 1130.56 | 1130.40 | -0.16 |
| West 310th Street | 1140.19 | 1140.15 | -0.04 | 1140.34 | 1140.33 | -0.01 | 1140.44 | 1140.43 | -0.01 | 1140.56 | 1140.56 | 0.00 | 1140.65 | 1140.64 | 0.00 | 1140.73 | 1140.73 | 0.00 |
| Branch A47 Connection to Branch A46 | 1128.52 | 1128.18 | -0.34 | 1128.66 | 1128.53 | -0.13 | 1129.01 | 1128.89 | -0.12 | 1129.59 | 1129.49 | -0.10 | 1130.07 | 1129.98 | -0.09 | 1130.56 | 1130.40 | -0.16 |
| Denotes peak elevation less than | | | | | | | | | | | | | | | | | | |

or equal to existing

MARTIN AND FARIBAULT COUNTIES JUDICIAL DITCH No. 414 January 28, 2020



Option 3 - 3ac Storage Pond

XP SWMM FLOWRATE TABLE

| ting Propose (cfs) (cfs) .00 262.63 .00 262.63 .00 262.63 .00 136.63 .00 136.63 .00 136.63 .00 136.63 .01 136.63 .02 12.41 .03 .04.41 | % Change 1% N/A | Existing (cfs) 528.00 528.00 528.00 271.00 0.00 271.00 11.66 | Proposed (cfs) 518.51 0.00 518.51 261.51 0.00 261.51 | % Change -2% N/A -2% -4% N/A | Existing (cfs) 760.00 0.00 760.00 389.00 | (cfs) 742.07 0.00 742.07 | % Change -2% N/A -2% | Existing (cfs) 1110.00 0.00 1110.00 | Proposed (cfs) 1076.19 0.00 | % Change -3% N/A | Existing (cfs) 1410.00 0.00 | Proposed (cfs) 1377.19 0.00 | % Change -2% N/A | Existing (cfs) 1760.00 0.00 | Proposed (cfs) 1763.33 0.00 | % Change 0% N/A |
|---|-------------------------------------|--|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 00 0.00 0.00 262.63 0.00 136.63 00 0.00 0.00 136.63 52 12.41 16 0.00 | N/A 1% 2% N/A 2% 63% | 0.00 528.00 271.00 0.00 271.00 | 0.00 518.51 261.51 0.00 | N/A -2% -4% | 0.00 760.00 | 0.00 742.07 | N/A | 0.00 | 0.00 | N/A | | | - | | | |
| .00 262.63 .00 136.63 .00 0.00 .00 136.63 .00 136.63 .00 136.63 .00 136.63 .00 136.63 .00 136.63 .00 136.63 .00 136.63 .00 136.00 | 1% 2% N/A 2% 63% | 528.00 271.00 0.00 271.00 | 518.51 261.51 0.00 | -2% -4% | 760.00 | 742.07 | | | | | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A |
| .00 136.63 00 0.00 .00 136.63 52 12.41 16 0.00 | 2% N/A 2% 63% | 271.00 0.00 271.00 | 261.51 0.00 | -4% | | | -2% | 1110.00 | 1070 10 | | | | | | | ,// |
| 00 0.00 00 136.63 52 12.41 16 0.00 | N/A 2% 63% | 0.00 271.00 | 0.00 | | 389.00 | 274 07 | | 1110.00 | 1076.19 | -3% | 1410.00 | 1377.19 | -2% | 1760.00 | 1763.33 | 0% |
| .00 136.63 52 12.41 16 0.00 | 2% 63% | 271.00 | | N/A | | 371.07 | -5% | 567.00 | 533.19 | -6% | 722.00 | 689.19 | -5% | 901.00 | 904.33 | 0% |
| 52 12.41 16 0.00 | 63% | | 261 51 | , | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A | 0.00 | 0.00 | N/A |
| 16 0.00 | | 11.66 | 201.01 | -4% | 389.00 | 371.07 | -5% | 567.00 | 533.19 | -6% | 722.00 | 689.19 | -5% | 901.00 | 904.33 | 0% |
| | -100% | - | 15.17 | 30% | 13.69 | 18.24 | 33% | 27.17 | 22.61 | -17% | 32.19 | 29.03 | -10% | 33.37 | 38.51 | 15% |
| 77 12 41 | | 13.24 | 0.24 | -98% | 23.19 | 0.70 | -97% | 41.18 | 11.94 | -71% | 58.39 | 28.74 | -51% | 77.19 | 75.38 | -2% |
| 77 12.41 | 27% | 24.90 | 15.40 | -38% | 36.88 | 18.95 | -49% | 68.35 | 34.55 | -49% | 90.58 | 57.77 | -36% | 110.55 | 113.89 | 3% |
| 26 8.46 | 572% | -0.93 | 8.45 | -1006% | -0.93 | 8.44 | -1013% | -0.87 | -3.59 | 315% | -0.87 | -3.30 | 281% | -0.86 | -3.07 | 256% |
| 03 6.19 | 54% | 6.42 | 9.35 | 46% | 8.90 | 13.15 | 48% | 12.83 | 18.48 | 44% | 16.27 | 23.57 | 45% | 19.77 | 28.52 | 44% |
| 29 14.65 | 177% | 5.49 | 17.80 | 224% | 7.98 | 21.59 | 171% | 11.96 | 14.89 | 24% | 15.40 | 20.28 | 32% | 18.91 | 25.45 | 35% |
| 34 1.44 | 72% | 0.85 | 1.44 | 70% | 0.85 | 1.44 | 70% | 0.83 | 1.44 | 73% | 0.82 | 1.44 | 75% | 0.82 | 1.45 | 77% |
| 51 0.00 | -100% | 0.75 | 0.06 | -92% | 1.13 | 0.20 | -83% | 1.77 | 0.53 | -70% | 2.41 | 0.83 | -66% | 3.05 | 1.16 | -62% |
| 35 1.44 | 7% | 1.60 | 1.50 | -6% | 1.98 | 1.64 | -17% | 2.60 | 1.97 | -24% | 3.23 | 2.27 | -30% | 3.87 | 2.61 | -33% |
| 52 4.05 | 552% | 0.63 | 3.09 | 393% | 0.63 | 2.83 | 350% | 0.63 | 2.82 | 347% | 0.63 | 2.78 | 340% | 0.63 | 2.86 | 352% |
| 53 5.26 | 738% | 0.81 | 8.75 | 976% | 1.02 | 10.53 | 934% | 1.04 | 12.28 | 1081% | 0.63 | 12.19 | 1834% | 0.56 | 11.99 | 2060% |
| | | 1.44 | | | | | | | 15.10 | | | | | 1.19 | | 1151% |
| 27 0.67 | 144% | 0.28 | 0.68 | | 0.28 | 0.68 | 143% | 0.28 | 0.68 | 144% | 0.28 | 0.68 | 143% | 0.28 | 0.68 | 143% |
| 20 1 1 10 | | | | | | | | | | | | | | | | 489% |
| - | 275% | 0.57 | 2.19 | 281% | 0.63 | 2.54 | 300% | 0.67 | 3.09 | 362% | 0.68 | 3.14 | 359% | 0.68 | 3.06 | 347% |
| | 0.67 | 0.67 144% 1.10 456% | 0.67 144% 0.28 1.10 456% 0.30 | 0.67 144% 0.28 0.68 1.10 456% 0.30 1.51 | 0.67 144% 0.28 0.68 147% 1.10 456% 0.30 1.51 404% | 0.67 144% 0.28 0.68 147% 0.28 1.10 456% 0.30 1.51 404% 0.35 | 0.67 144% 0.28 0.68 147% 0.28 0.68 1.10 456% 0.30 1.51 404% 0.35 1.86 | 0.67 144% 0.28 0.68 147% 0.28 0.68 143% 1.10 456% 0.30 1.51 404% 0.35 1.86 424% | 0.67 144% 0.28 0.68 147% 0.28 0.68 143% 0.28 1.10 456% 0.30 1.51 404% 0.35 1.86 424% 0.39 | 0.67 144% 0.28 0.68 147% 0.28 0.68 143% 0.28 0.68 1.10 456% 0.30 1.51 404% 0.35 1.86 424% 0.39 2.41 | 0.67 144% 0.28 0.68 147% 0.28 0.68 143% 0.28 0.68 144% 1.10 456% 0.30 1.51 404% 0.35 1.86 424% 0.39 2.41 518% | 0.67 144% 0.28 0.68 147% 0.28 0.68 143% 0.28 0.68 144% 0.28 1.10 456% 0.30 1.51 404% 0.35 1.86 424% 0.39 2.41 518% 0.40 | 0.67 144% 0.28 0.68 147% 0.28 0.68 143% 0.28 0.68 144% 0.28 0.68 1.10 456% 0.30 1.51 404% 0.35 1.86 424% 0.39 2.41 518% 0.40 2.46 | 0.67 144% 0.28 0.68 147% 0.28 0.68 143% 0.28 0.68 144% 0.28 0.68 144% 1.10 456% 0.30 1.51 404% 0.35 1.86 424% 0.39 2.41 518% 0.40 2.46 509% | 0.67 144% 0.28 0.68 147% 0.28 0.68 143% 0.28 0.68 144% 0.28 0.68 143% 0.28 1.10 456% 0.30 1.51 404% 0.35 1.86 424% 0.39 2.41 518% 0.40 2.46 509% 0.40 | 0.67 144% 0.28 0.68 147% 0.28 0.68 143% 0.28 0.68 144% 0.28 0.68 143% 0.28 0.68 144% 0.28 0.68 143% 0.28 0.68 144% 0.28 0.68 143% <th< td=""></th<> |

equal to existing

MARTIN AND FARIBAULT COUNTIES JUDICIAL DITCH No. 414 February 6, 2020



Option 3 - 3ac Storage Pond

XP SWMM ELEVATION TABLE

| | 2-yr | | | 5-yr | | | 10-yr | | | 25-yr | | | 50-yr | | | 100-yr | | |
|--|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|-------------------|-------------------|------------|
| Location | Existing (MSL) | Proposed (MSL) | Difference |
| Branch A40 Outlet - JD 414 Open Ditch | 1117.70 | 1115.70 | -2.00 | 1118.37 | 1115.78 | -2.59 | 1118.67 | 1115.86 | -2.81 | 1120.39 | 1115.97 | -4.43 | 1120.95 | 1116.10 | -4.86 | 1121.08 | 1116.26 | -4.82 |
| Branch A41 Connection to Branch A40 | 1125.72 | 1125.77 | 0.04 | 1126.04 | 1125.88 | -0.15 | 1126.36 | 1126.29 | -0.07 | 1126.73 | 1126.73 | 0.00 | 1127.08 | 1126.98 | -0.10 | 1127.54 | 1127.19 | -0.36 |
| North CSAH 2 | 1127.94 | 1128.08 | 0.14 | 1128.45 | 1128.52 | 0.07 | 1128.88 | 1128.89 | 0.01 | 1129.49 | 1129.48 | -0.01 | 1129.97 | 1129.98 | 0.00 | 1130.33 | 1130.39 | 0.06 |
| South CSAH 2 | 1128.26 | 1128.11 | -0.16 | 1128.66 | 1128.53 | -0.13 | 1129.01 | 1128.89 | -0.12 | 1129.59 | 1129.49 | -0.10 | 1130.07 | 1129.98 | -0.09 | 1130.56 | 1130.40 | -0.15 |
| West 310th Street | 1140.19 | 1140.15 | -0.04 | 1140.34 | 1140.33 | -0.01 | 1140.44 | 1140.43 | -0.01 | 1140.56 | 1140.56 | 0.00 | 1140.65 | 1140.64 | 0.00 | 1140.73 | 1140.73 | 0.00 |
| Branch A47 Connection to Branch A46 | 1128.52 | 1128.18 | -0.34 | 1128.66 | 1128.53 | -0.13 | 1129.01 | 1128.89 | -0.12 | 1129.59 | 1129.49 | -0.10 | 1130.07 | 1129.98 | -0.09 | 1130.56 | 1130.40 | -0.15 |
| Denotes peak elevation less than | | | | | | | | | | | | | | | | | | |

or equal to existing




Figure 2: 2-year Rainfall Event Existing Flood Extents




Figure 1: 2-year Rainfall Event Existing Flood Inundation Times




Figure 4: 2-year Rainfall Event Option 1 Flood Extents



Figure 3: 2-year Rainfall Event Option 1 Inundation Times




Figure 6: 2-year Rainfall Event Option 2 Flood Extents



Figure 5: 2-year Rainfall Event Option 2 Inundation Times




Figure 8: 2-year Rainfall Event Option 3 Flood Extents



Figure 7: 2-year Rainfall Event Option 3 Inundation Times




Figure 10: 10-year Rainfall Event Existing Flood Extents




Figure 9: 10-year Rainfall Event Existing Indunation Times




Figure 11: 10-year Rainfall Event Option 1 Flood Extents

Figure 12: 10-year Rainfall Event Option 1 Inundation Times




Figure 16: 10-year Rainfall Event Option 2 Flood Extents



Figure 15: 10-year Rainfall Event Option 2 Inundation Times




Figure 14: 10-year Rainfall Event Option 3 Flood Extents



Figure 13: 10-year Rainfall Event Option 3 Indunation Times

Appendix F: Preliminary Cost Estimate

MARTIN AND FARIBAULT COUNTIES JUDICIAL DITCH No. 414

ISG

PROPOSED IMPROVEMENT COST SUMMARY OPTION 1 - TILE IMPROVEMENT

| Area | Separable Maintenance | Im | provement Cost | Net Cost |
|---------------------------------|--------------------------|-------------|-----------------|---------------|
| Branch A40 Tile | \$ 230,091 | \$ | 332,751 | \$ 102,661 |
| Branch A43 Tile | \$ 25,787 | \$ | 33,372 | \$ 7,586 |
| Branch A45 Tile | \$ 25,653 | \$ | 27,561 | \$ 1,908 |
| Branch A46 Tile | \$ 58,117 | \$ | 70,993 | \$ 12,876 |
| Branch A47 Tile | \$ 12,409 | \$ | 17,827 | \$ 5,418 |
| Subtotal without Road Crossings | \$ 352,056 | \$ | 482,504 | \$ 130,448 |
| Road Authority Cost | \$ 11,292 | \$ | 11,292 | \$ - |
| Damages Paid To Road Authority | \$ 6,902 | \$ | 26,773 | \$ 19,870 |
| Total | \$ 370,251 | \$ | 520,568 | \$ 150,318 |
| | Subt | otal | Landowner Costs | \$ 509,277 |
| | | | Net Costs | \$ 150,318 |
| | Viewers Costs | \$ 3,000 | | |
| | Total Project Co | sts | for Landowners | \$ 512,277 |

OPTION 2 - TILE IMPROVEMENT W/ 1-AC STORAGE

| Area | Separable Maintenance | Im | provement Cost | Net Cost |
|---------------------------------|--------------------------|---------------|-----------------|---------------|
| Tile Improvement | \$ 352,056 | \$ | 482,504 | \$ 130,448 |
| Storage - 1 AC | \$ - | \$ | 92,087 | \$ 92,087 |
| Subtotal without Road Crossings | \$ 352,056 | \$ | 574,591 | \$ 222,535 |
| Road Authority Cost | \$ 11,292 | \$ | 11,292 | \$ - |
| Damages Paid To Road Authority | \$ 6,902 | \$ | 26,773 | \$ 19,870 |
| Total | \$ 370,251 | \$ | 612,656 | \$ 242,405 |
| | Subt | otal | Landowner Costs | \$ 601,364 |
| | Net Costs | \$ 242,405 | | |
| | Viewers Cost | \$ 3,000 | | |
| | Total Project Co | sts | for Landowners | \$ 604,364 |

OPTION 3 - TILE IMPROVEMENT W/ 3-AC STORAGE

| Area | Separable Maintenance | Im | provement Cost | Net Cost |
|---------------------------------|--------------------------|-------------|-----------------|---------------|
| Tile Improvement | \$ 352,056 | \$ | 482,504 | \$ 130,448 |
| Storage - 3 AC | \$ - | \$ | 216,128 | \$ 216,128 |
| Subtotal without Road Crossings | \$ 352,056 | \$ | 698,632 | \$ 346,575 |
| Road Authority Cost | \$ 11,292 | \$ | 11,292 | \$ - |
| Damages Paid To Road Authority | \$ 6,902 | \$ | 26,773 | \$ 19,870 |
| Total | \$ 370,251 | \$ | 736,696 | \$ 366,445 |
| | Subt | otal | Landowner Costs | \$ 725,404 |
| | | | Net Costs | \$ 366,445 |
| | Viewers Cost | \$ 3,000 | | |
| | Total Project Co | sts | for Landowners | \$ 728,404 |

SEPARABLE MAINTANENCE (REPAIR)

Branch A40 Tile

| Item No. | ltem | Unit | Quantity | U | Init Price | | Amount | |
|-----------------------------------|--|----------|-------------|------|------------|----|---------|--|
| 101 | MOBILIZATION | LS | 1 | \$ | 6,980.00 | \$ | 6,980 | |
| 102 | TILE INVESTIGATION | HR | 14 | \$ | 130.60 | \$ | 1,828 | |
| 103 | 15-INCH AGRICULTURAL TILE | LF | 1100 | \$ | 19.50 | \$ | 21,450 | |
| 104 | 12-INCH AGRICULTURAL TILE | LF | 2400 | \$ | 17.30 | \$ | 41,520 | |
| 105 | 10-INCH AGRICULTURAL TILE | LF | 1000 | \$ | 16.70 | \$ | 16,700 | |
| 106 | 8-INCH AGRICULTURAL TILE | LF | 2350 | \$ | 14.60 | \$ | 34,310 | |
| 107 | CONNECT EXISTING 18-INCH TILE | EA | 1 | \$ | 876.80 | \$ | 877 | |
| 108 | CONNECT EXISTING 15-INCH TILE | EA | 1 | \$ | 697.40 | \$ | 697 | |
| 109 | CONNECT EXISTING 10-INCH TILE | EA | 1 | \$ | 580.20 | \$ | 580 | |
| 110 | CONNECT EXISTING 8-INCH TILE | EA | 2 | \$ | 465.70 | \$ | 931 | |
| 111 | 15-INCH CROSS-CONNECT W/30 LF OF SPECIFIED PIPE | EA | 1 | \$ | 1,073.80 | \$ | 1,074 | |
| 112 | 12-INCH CROSS-CONNECT W/30 LF OF SPECIFIED PIPE | EA | 2 | \$ | 1,049.00 | \$ | 2,098 | |
| 113 | 15-INCH TILE OUTLET (20 LF OF PIPE & RIPRAP ON GEOTEXTILE FABRIC) | EA | 1 | \$ | 1,170.70 | \$ | 1,171 | |
| 114 | GRANULAR PIPE FOUNDATION | CY | 427 | \$ | 24.30 | \$ | 10,386 | |
| 115 | INSTALL DROP INTAKE (18-INCH) | EA | 7 | \$ | 988.50 | \$ | 6,920 | |
| 116 | CAP DROP INTAKE (18-INCH) | EA | 2 | \$ | 224.70 | \$ | 449 | |
| 117 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 28 | \$ | 500.00 | \$ | 14,000 | |
| | | | | | TOTAL | \$ | 162,000 | |
| | | | 10% | 6 UN | IFORSEEN | \$ | 16,200 | |
| | | | | 9, | SUBTOTAL | \$ | 178,200 | |
| | TEMPORARY DAMAGES | AC | 15.73 | \$ | 650.00 | \$ | 10,222 | |
| | | COUNTY | ADMINISTR | ATI | ON COSTS | \$ | 8,910 | |
| TOPOGRAPHIC SURVEY | | | | | | | | |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | | |
| | CONSTRUC | CTION ST | AKING & ADI | MINI | STRATION | \$ | 13,365 | |
| | TOT | AL BRAN | CH A40 TILE | REF | PAIR COST | \$ | 230,091 | |

Branch A43 Tile

| Item No. | Item | Unit | Quantity | U | nit Price | Amount |
|----------|--|-----------|-------------|-------|-----------|--------------|
| 101 | MOBILIZATION | LS | 1 | \$ | 780.00 | \$ 780 |
| 102 | TILE INVESTIGATION | HR | 2 | \$ | 130.60 | \$ 261 |
| 103 | 8-INCH AGRICULTURAL TILE | LF | 800 | \$ | 14.60 | \$ 11,680 |
| 104 | CONNECT EXISTING 10-INCH TILE | EA | 1 | \$ | 580.20 | \$ 580 |
| 105 | CONNECT EXISTING 8-INCH TILE | EA | 1 | \$ | 465.70 | \$ 466 |
| 106 | GRANULAR PIPE FOUNDATION | CY | 45 | \$ | 24.30 | \$ 1,092 |
| 107 | INSTALL DROP INTAKE (18-INCH) | EA | 1 | \$ | 988.50 | \$ 989 |
| 108 | CAP DROP INTAKE (18-INCH) | EA | 1 | \$ | 224.70 | \$ 225 |
| 109 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 4 | \$ | 500.00 | \$ 2,000 |
| | | | | | TOTAL | 18,100 |
| | | | 10% | 6 UN | FORSEEN | \$ 1,810 |
| | | | | S | UBTOTAL | \$ 19,910 |
| | TEMPORARY DAMAGES | AC | 1.84 | \$ | 650.00 | \$ 1,194 |
| | | COUNTY | ADMINISTR | ATIC | ON COSTS | \$ 996 |
| | | | TOPOGRA | PHIC | C SURVEY | \$ 600 |
| | REPC | ORTS, PLA | ANS AND SP | ECIF | ICATIONS | \$ 1,593 |
| | CONSTRUC | CTION ST | AKING & ADI | MINIS | STRATION | \$ 1,494 |
| | TOT | AL BRAN | CH A43 TILE | REP | AIR COST | \$ 25,787 |

SEPARABLE MAINTANENCE (REPAIR)

Branch A45 Tile

| Item No. | Item | Unit | Quantity | U | nit Price | | Amount |
|-----------------------------------|--|----------|-------------|-------|-----------|----|--------|
| 101 | MOBILIZATION | LS | 1 | \$ | 780.00 | \$ | 780 |
| 102 | TILE INVESTIGATION | HR | 2 | \$ | 130.60 | \$ | 261 |
| 103 | 8-INCH AGRICULTURAL TILE | LF | 800 | \$ | 14.60 | \$ | 11,680 |
| 104 | CONNECT EXISTING 8-INCH TILE | EA | 2 | \$ | 465.70 | \$ | 931 |
| 105 | GRANULAR PIPE FOUNDATION | CY | 45 | \$ | 24.30 | \$ | 1,092 |
| 106 | INSTALL DROP INTAKE (18-INCH) | EA | 1 | \$ | 988.50 | \$ | 989 |
| 107 | CAP DROP INTAKE (18-INCH) | EA | 1 | \$ | 224.70 | \$ | 225 |
| 108 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 4 | \$ | 500.00 | \$ | 2,000 |
| | | | | | TOTAL | \$ | 18,000 |
| | | | 10% | 6 UN | FORSEEN | \$ | 1,800 |
| | | | | S | UBTOTAL | \$ | 19,800 |
| | TEMPORARY DAMAGES | AC | 1.84 | \$ | 650.00 | \$ | 1,194 |
| | | COUNTY | ADMINISTR | ATIC | ON COSTS | \$ | 990 |
| | | | TOPOGRA | PHIC | C SURVEY | \$ | 600 |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | |
| | CONSTRUC | CTION ST | AKING & ADI | MINIS | STRATION | \$ | 1,485 |
| | TOT | AL BRAN | CH A45 TILE | REP | AIR COST | \$ | 25,653 |

Branch A46 Tile

| Item No. | ltem | Unit | Quantity | Unit Price | | Amount | | |
|-----------------------------------|--|----------|-------------|--------------------|----|--------|--|--|
| 101 | MOBILIZATION | LS | 1 | \$ 1,760.00 | \$ | 1,760 | | |
| 102 | TILE INVESTIGATION | HR | 4 | \$ 130.60 | \$ | 522 | | |
| 103 | 10-INCH AGRICULTURAL TILE | LF | 600 | \$ 16.70 | \$ | 10,020 | | |
| 104 | 8-INCH AGRICULTURAL TILE | LF | 1200 | \$ 14.60 | \$ | 17,520 | | |
| 105 | CONNECT EXISTING 8-INCH TILE | EA | 3 | \$ 465.70 | \$ | 1,397 | | |
| 106 | 8-INCH CROSS-CONNECT W/30 LF OF SPECIFIED PIPE | EA | 1 | \$ 775.40 | \$ | 775 | | |
| 107 | GRANULAR PIPE FOUNDATION | CY | 103 | \$ 24.30 | \$ | 2,515 | | |
| 108 | INSTALL DROP INTAKE (18-INCH) | EA | 2 | \$ 988.50 | \$ | 1,977 | | |
| 109 | CAP DROP INTAKE (18-INCH) | EA | 1 | \$ 224.70 | \$ | 225 | | |
| 110 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 8 | \$ 500.00 | \$ | 4,000 | | |
| | | | | TOTAL | \$ | 40,800 | | |
| | | | 10% | 6 UNFORSEEN | \$ | 4,080 | | |
| | | | | SUBTOTAL | \$ | 44,880 | | |
| | TEMPORARY DAMAGES | AC | 4.13 | \$ 650.00 | \$ | 2,686 | | |
| | | COUNTY | ' ADMINISTR | ATION COSTS | \$ | 2,244 | | |
| TOPOGRAPHIC SURVEY | | | | | | | | |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | | |
| | CONSTRUC | CTION ST | AKING & ADI | MINISTRATION | \$ | 3,366 | | |
| | TOT | AL BRAN | CH A46 TILE | REPAIR COST | \$ | 58,117 | | |



SEPARABLE MAINTANENCE (REPAIR)

Branch A47 Tile

| Item No. | Item | Unit | Quantity | J | nit Price | | Amount | |
|-----------------------------------|--|---------|-------------|------|-----------------|----|--------|--|
| 101 | MOBILIZATION | LS | 1 | \$ | 370.00 | \$ | 370 | |
| 102 | TILE INVESTIGATION | HR | 1 | \$ | 130.60 | \$ | 131 | |
| 103 | 6-INCH AGRICULTURAL TILE | LF | 450 | \$ | 9.90 | \$ | 4,455 | |
| 104 | CONNECT EXISTING 8-INCH TILE | EA | 1 | \$ | 465.70 | \$ | 466 | |
| 105 | CONNECT EXISTING 6-INCH TILE | EA | 1 | \$ | 377.90 | \$ | 378 | |
| 106 | GRANULAR PIPE FOUNDATION | CY | 24 | \$ | 24.30 | \$ | 574 | |
| 107 | INSTALL DROP INTAKE (18-INCH) | EA | 1 | \$ | 988.50 | \$ | 989 | |
| 108 | CAP DROP INTAKE (18-INCH) | EA | 1 | \$ | 224.70 | \$ | 225 | |
| 109 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 2 | \$ | 500.00 | \$ | 1,000 | |
| | | | | | TOTAL | \$ | 8,600 | |
| | | | 10% | 6 UN | FORSEEN | \$ | 860 | |
| | | | | S | SUBTOTAL | \$ | 9,460 | |
| | TEMPORARY DAMAGES | AC | 1.03 | \$ | 650.00 | \$ | 671 | |
| | | COUNTY | ADMINISTR | ATIC | ON COSTS | \$ | 473 | |
| | | | TOPOGRA | PHI | C SURVEY | \$ | 338 | |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | | |
| | CONSTRUCTION STAKING & ADMINISTRATION | | | | | | | |
| | TOT | AL BRAN | CH A47 TILE | REP | PAIR COST | \$ | 12,409 | |

TOTAL REPAIR COST

| Branch A40 Tile | \$ 230,091 |
|----------------------|---------------|
| Branch A43 Tile | \$ 25,787 |
| Branch A45 Tile | \$ 25,653 |
| Branch A46 Tile | \$ 58,117 |
| Branch A47 Tile | \$ 12,409 |
| | |
| COMPLETE REPAIR COST | \$ 352.056 |

PROPOSED IMPROVEMENT

Branch A40 Tile

| Item No. | Item | Unit | Quantity | U | Init Price | | Amount | | |
|-----------------------------------|---|---------|------------|-----|------------|----|-----------------|--|--|
| 101 | MOBILIZATION | LS | 1 | \$ | 10,260.00 | \$ | 10,260 | | |
| 102 | TILE INVESTIGATION | HR | 13 | \$ | 130.60 | \$ | 1,698 | | |
| 104 | 24-INCH AGRICULTURAL TILE | LF | 4245 | \$ | 32.70 | \$ | 138,812 | | |
| 105 | 18-INCH AGRICULTURAL TILE | LF | 100 | \$ | 22.50 | \$ | 2,250 | | |
| 106 | 15-INCH AGRICULTURAL TILE | LF | 410 | \$ | 19.50 | \$ | 7,995 | | |
| 105 | 12-INCH AGRICULTURAL TILE | LF | 1220 | \$ | 17.30 | \$ | 21,106 | | |
| 107 | 8-INCH AGRICULTURAL TILE | LF | 451 | \$ | 14.60 | \$ | 6,585 | | |
| 108 | CONNECT EXISTING 18-INCH TILE | EA | 1 | \$ | 876.80 | \$ | 877 | | |
| 109 | CONNECT EXISTING 15-INCH TILE | EA | 1 | \$ | 697.40 | \$ | 697 | | |
| 110 | CONNECT EXISTING 10-INCH TILE | EA | 1 | \$ | 580.20 | \$ | 580 | | |
| 111 | CONNECT EXISTING 8-INCH TILE | EA | 2 | \$ | 465.70 | \$ | 931 | | |
| 112 | 15-INCH CROSS-CONNECT W/30 LF OF SPECIFIED PIPE | EA | 1 | \$ | 1,073.80 | \$ | 1,074 | | |
| 113 | 12-INCH CROSS-CONNECT W/30 LF OF SPECIFIED PIPE | EA | 2 | \$ | 1,049.00 | \$ | 2,098 | | |
| 114 | 24-INCH TILE OUTLET | EA | 1 | \$ | 1,658.60 | \$ | 1,659 | | |
| 114 | (20 LF OF PIPE & RIPRAP ON GEOTEXTILE FABRIC) | EA | I | φ | 1,058.00 | φ | 1,059 | | |
| 116 | FURNISH & INSTALL WATER QUALITY INLET | EA | 4 | \$ | 1,152.60 | \$ | 4,610 | | |
| 117 | INSTALL 12-INCH PERFORATED TILE | LF | 158 | \$ | 13.00 | \$ | 2,054 | | |
| 118 | GRANULAR PIPE FOUNDATION | CY | 517 | \$ | 24.30 | \$ | 12,559 | | |
| 119 | INSTALL DROP INTAKE (18-INCH) | EA | 9 | \$ | 988.50 | \$ | 8,897 | | |
| 120 | CAP DROP INTAKE (18-INCH) | EA | 2 | \$ | 224.70 | \$ | 449 | | |
| 121 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 26 | \$ | 500.00 | \$ | 13,000 | | |
| | | | | | TOTAL | \$ | 238,190 | | |
| | | | 10% | - | FORSEEN | Ţ | 23,819 | | |
| | | | | | SUBTOTAL | | 262,009 | | |
| ļ | TEMPORARY DAMAGES | AC | 14.75 | \$ | 650.00 | \$ | 9,589 13,101 | | |
| COUNTY ADMINISTRATION COSTS | | | | | | | | | |
| | | | | | | | | | |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | | | |
| | CONSTRUCTION STAKING & ADMINISTRATION TOTAL BRANCH A40 TILE IMPROVEMENT COST | | | | | | | | |
| | TOTAL BRA | NCH A40 | TILE IMPRO | VEM | ENT COST | \$ | 332,751 | | |

Branch A43 Tile

| Item No. | ltem | Unit | Quantity | U | nit Price | | Amount |
|---------------------------------------|--|---------|------------|------------|-----------|----|--------|
| 101 | MOBILIZATION | LS | 1 | \$ | 1,040.00 | \$ | 1,040 |
| 102 | TILE INVESTIGATION | HR | 2 | \$ | 130.60 | \$ | 261 |
| 103 | 15-INCH AGRICULTURAL TILE | LF | 870 | \$ | 19.50 | \$ | 16,965 |
| 104 | CONNECT EXISTING 10-INCH TILE | EA | 1 | \$ | 580.20 | \$ | 580 |
| 105 | CONNECT EXISTING 8-INCH TILE | EA | 1 | \$ | 465.70 | \$ | 466 |
| 106 | GRANULAR PIPE FOUNDATION | CY | 62 | \$ | 24.30 | \$ | 1,507 |
| 107 | INSTALL DROP INTAKE (18-INCH) | EA | 1 | \$ | 988.50 | \$ | 989 |
| 108 | CAP DROP INTAKE (18-INCH) | EA | 1 | \$ | 224.70 | \$ | 225 |
| 109 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 4 | \$ | 500.00 | \$ | 2,000 |
| | | | | | TOTAL | | 24,033 |
| | | | 10% | 6 UN | IFORSEEN | \$ | 2,403 |
| | | | | 9 | SUBTOTAL | \$ | 26,436 |
| | TEMPORARY DAMAGES | AC | 2.00 | \$ | 650.00 | \$ | 1,298 |
| | | COUNTY | ADMINISTF | RATIO | ON COSTS | \$ | 1,322 |
| | | | TOPOGRA | PHI | C SURVEY | \$ | 653 |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | |
| CONSTRUCTION STAKING & ADMINISTRATION | | | | | | | |
| | TOTAL BRA | NCH A43 | TILE IMPRO | VEM | ENT COST | \$ | 34,072 |

PROPOSED IMPROVEMENT

Branch A45 Tile

| Item No. | Item | Unit | Quantity | Uı | nit Price | | Amount | |
|----------|--|----------|------------|-------|-----------|----|--------|--|
| 101 | MOBILIZATION | LS | 1 | \$ | 830.00 | \$ | 830 | |
| 102 | TILE INVESTIGATION | HR | 2 | \$ | 130.60 | \$ | 261 | |
| 103 | 8-INCH AGRICULTURAL TILE | LF | 872 | \$ | 14.60 | \$ | 12,731 | |
| 104 | CONNECT EXISTING 8-INCH TILE | EA | 2 | \$ | 465.70 | \$ | 931 | |
| 106 | GRANULAR PIPE FOUNDATION | CY | 49 | \$ | 24.30 | \$ | 1,191 | |
| 107 | INSTALL DROP INTAKE (18-INCH) | EA | 1 | \$ | 988.50 | \$ | 989 | |
| 108 | CAP DROP INTAKE (18-INCH) | EA | 1 | \$ | 224.70 | \$ | 225 | |
| 109 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 4 | \$ | 500.00 | \$ | 2,000 | |
| | | | | | TOTAL | | 19,158 | |
| | | | 10% | 6 UN | FORSEEN | \$ | 1,916 | |
| | | | | S | UBTOTAL | \$ | 21,073 | |
| | TEMPORARY DAMAGES | AC | 2.00 | \$ | 650.00 | \$ | 1,301 | |
| | | COUNTY | ADMINIST | RATIC | ON COSTS | \$ | 1,054 | |
| | | | TOPOGRA | PHIC | C SURVEY | \$ | 654 | |
| | REPORTS, PLANS AND SPECIFICATIONS | | | | | | | |
| | CONSTRU | CTION ST | AKING & AD | MINIS | STRATION | \$ | 1,581 | |
| | TOTAL BRA | NCH A45 | TILE IMPRO | VEME | ENT COST | \$ | 27,561 | |

Branch A46 Tile

| Item No. | ltem | Unit | Quantity | U | Init Price | | Amount | |
|--------------------|--|----------|-------------|------|------------|----|--------|--|
| 101 | MOBILIZATION | LS | 1 | \$ | 2,160.00 | \$ | 2,160 | |
| 102 | TILE INVESTIGATION | HR | 4 | \$ | 130.60 | \$ | 522 | |
| 103 | 18-INCH AGRICULTURAL TILE | LF | 600 | \$ | 22.50 | \$ | 13,500 | |
| 104 | 15-INCH AGRICULTURAL TILE | LF | 500 | \$ | 19.50 | \$ | 9,750 | |
| 105 | 10-INCH AGRICULTURAL TILE | LF | 200 | \$ | 16.70 | \$ | 3,340 | |
| 106 | 8-INCH AGRICULTURAL TILE | LF | 567 | \$ | 14.60 | \$ | 8,278 | |
| 107 | CONNECT EXISTING 8-INCH TILE | EA | 3 | \$ | 465.70 | \$ | 1,397 | |
| 108 | 8-INCH CROSS-CONNECT W/30 LF OF SPECIFIED PIPE | EA | 1 | \$ | 775.40 | \$ | 775 | |
| 109 | GRANULAR PIPE FOUNDATION | CY | 126 | \$ | 24.30 | \$ | 3,071 | |
| 110 | INSTALL DROP INTAKE (18-INCH) | EA | 3 | \$ | 988.50 | \$ | 2,966 | |
| 111 | CAP DROP INTAKE (18-INCH) | EA | 1 | \$ | 224.70 | \$ | 225 | |
| 112 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 8 | \$ | 500.00 | \$ | 4,000 | |
| - | | | - | | TOTAL | | 49,984 | |
| | | | 10% | 6 UN | FORSEEN | \$ | 4,998 | |
| | | | | 9 | SUBTOTAL | \$ | 54,983 | |
| | TEMPORARY DAMAGES | AC | 4.29 | \$ | 650.00 | \$ | 2,786 | |
| | | COUNTY | Y ADMINISTF | RATI | ON COSTS | \$ | 2,750 | |
| TOPOGRAPHIC SURVEY | | | | | | | | |
| | | | ANS AND SP | | | | 4,949 | |
| | CONSTRU | CTION ST | AKING & AD | MINI | STRATION | \$ | 4,124 | |
| | TOTAL BRA | NCH A46 | TILE IMPRO | VEM | ENT COST | \$ | 70,993 | |

PROPOSED IMPROVEMENT

Branch A47 Tile

| Item No. | ltem | Unit | Quantity | U | nit Price | | Amount | | |
|-----------------------------------|--|--------|------------|------------|-----------|----|--------|--|--|
| 101 | MOBILIZATION | LS | 1 | \$ | 540.00 | \$ | 540 | | |
| 102 | TILE INVESTIGATION | HR | 2 | \$ | 130.60 | \$ | 261 | | |
| 103 | 8-INCH AGRICULTURAL TILE | LF | 509 | \$ | 14.60 | \$ | 7,431 | | |
| 104 | CONNECT EXISTING 8-INCH TILE | EA | 1 | \$ | 465.70 | \$ | 466 | | |
| 105 | CONNECT EXISTING 6-INCH TILE | EA | 1 | \$ | 377.90 | \$ | 378 | | |
| 106 | GRANULAR PIPE FOUNDATION | CY | 29 | \$ | 24.30 | \$ | 695 | | |
| 107 | INSTALL DROP INTAKE (18-INCH) | EA | 1 | \$ | 988.50 | \$ | 989 | | |
| 108 | CAP DROP INTAKE (18-INCH) | EA | 1 | \$ | 224.70 | \$ | 225 | | |
| 109 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 3 | \$ | 500.00 | \$ | 1,500 | | |
| | | | | | TOTAL | \$ | 12,484 | | |
| | | | 10% | 6 UN | IFORSEEN | \$ | 1,248 | | |
| | | | | 0, | SUBTOTAL | \$ | 13,733 | | |
| | TEMPORARY DAMAGES | AC | 1.17 | \$ | 650.00 | | 760 | | |
| | | COUNTY | ADMINISTF | RATIO | ON COSTS | \$ | 687 | | |
| | | | TOPOGRA | PHI | C SURVEY | \$ | 382 | | |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | | | |
| | | | AKING & AD | | | | 1,030 | | |
| | TOTAL BRANCH A47 TILE IMPROVEMENT COST | | | | | | | | |

Storage - 1.0 AC

| Item No. | Item | Unit | Quantity | ι | Jnit Price | | Amount | | | |
|---------------------------------------|--|-------|-------------|------|------------|----|--------|--|--|--|
| 101 | MOBILIZATION | LS | 1 | \$ | 2,640.00 | \$ | 2,640 | | | |
| 102 | COMMON EXCAVATION (P) (EV) | CY | 14520 | \$ | 2.30 | \$ | 33,396 | | | |
| 103 | INSTALL STRUCTURE S-1 WITH GALVINIZED GRATE | LS | 1 | \$ | 14,462.30 | \$ | 14,462 | | | |
| 104 | 24-INCH CLASS III RCP PIPE | LF | 36 | \$ | 63.00 | \$ | 2,268 | | | |
| 105 | 15-INCH CLASS III RCP PIPE | LF | 24 | \$ | 35.00 | \$ | 840 | | | |
| 106 | CLASS III RIPRAP WITH GEOTEXTILE FABRIC | CY | 50 | \$ | 75.90 | \$ | 3,795 | | | |
| 107 | 16.5' BUFFER STRIP SEEDING (SEED MIX: BUFFER BLEND WITH TYPE 3 MULCH) | AC | 0.32 | \$ | 1,368.20 | \$ | 441 | | | |
| 108 | STANDARD SIDESLOPE SEEDING (SEED MIX: BUFFER BLEND WITH TYPE 8 MULCH) | AC | 0.35 | \$ | 2,958.50 | \$ | 1,039 | | | |
| 109 | STANDARD POND BOTTOM SEEDING (SEED MIX: 24-261 W/ TYPE 7 (BFM) MULCH) | AC | 0.65 | \$ | 3,450.00 | \$ | 2,238 | | | |
| | | | | | TOTAL | \$ | 61,119 | | | |
| | | | 10% | 6 UN | VFORSEEN | \$ | 6,112 | | | |
| | | | | , | SUBTOTAL | \$ | 67,231 | | | |
| | TEMPORARY DAMAGES | AC | 6.00 | \$ | 650.00 | \$ | 3,900 | | | |
| | LAND ACQUISTION/ PERMANENT DAMAGES | AC | 1.00 | \$ | 6,500.00 | \$ | 6,500 | | | |
| | | COUNT | Y ADMINISTF | RATI | ON COSTS | \$ | 3,362 | | | |
| TOPOGRAPHIC SURVEY | | | | | | | | | | |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | | | | |
| CONSTRUCTION STAKING & ADMINISTRATION | | | | | | | | | | |
| | TOTAL STORAGE - 1.0 AC IMPROVEMENT COST | | | | | | | | | |

PROPOSED IMPROVEMENT Storage - 3.0 AC

| Storage - 3.0 AC | | | | | | | | | | |
|---------------------------------------|--|-----------|-------------|------|------------|----|---------|--|--|--|
| Item No. | Item | Unit | Quantity | ι | Init Price | | Amount | | | |
| 101 | MOBILIZATION | LS | 1 | \$ | 5,960.00 | \$ | 5,960 | | | |
| 102 | COMMON EXCAVATION (P) (EV) | CY | 43560 | \$ | 2.30 | \$ | 100,188 | | | |
| 103 | INSTALL STRUCTURE S-1 WITH GALVINIZED GRATE | LS | 1 | \$ | 14,462.30 | \$ | 14,462 | | | |
| 104 | 24-INCH CLASS III RCP PIPE | LF | 36 | \$ | 63.00 | \$ | 2,268 | | | |
| 105 | 15-INCH CLASS III RCP PIPE | LF | 24 | \$ | 35.00 | \$ | 840 | | | |
| 106 | CLASS III RIPRAP WITH GEOTEXTILE FABRIC | CY | 50 | \$ | 75.90 | \$ | 3,795 | | | |
| 107 | 16.5' BUFFER STRIP SEEDING (SEED MIX: BUFFER BLEND WITH TYPE 3 MULCH) | AC | 0.60 | \$ | 1,368.20 | \$ | 825 | | | |
| 108 | STANDARD SIDESLOPE SEEDING (SEED MIX: BUFFER BLEND WITH TYPE 8 MULCH) | AC | 0.66 | \$ | 2,958.50 | \$ | 1,946 | | | |
| 109 | STANDARD POND BOTTOM SEEDING (SEED MIX: 24-261 W/ TYPE 7 (BFM) MULCH) | AC | 2.34 | \$ | 3,450.00 | \$ | 8,080 | | | |
| | | | | | TOTAL | | 138,365 | | | |
| | | | 10% | | NFORSEEN | | 13,837 | | | |
| | | | | | SUBTOTAL | | 152,202 | | | |
| | TEMPORARY DAMAGES | AC | 18.00 | \$ | 650.00 | \$ | 11,700 | | | |
| | LAND ACQUISTION/ PERMANENT DAMAGES | AC | 3.00 | \$ | 6,500.00 | \$ | 19,500 | | | |
| | | COUNT | Y ADMINISTF | RATI | ON COSTS | \$ | 7,611 | | | |
| TOPOGRAPHIC SURVEY | | | | | | | | | | |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | | | | |
| CONSTRUCTION STAKING & ADMINISTRATION | | | | | | | | | | |
| | TOTAL STO | RAGE - 3. | 0 AC IMPRO | VEN | IENT COST | \$ | 216,128 | | | |

PROPOSED IMPROVEMENT

IMPROVEMENT - OPTION 1

| Branch A40 Tile | \$ 332,751 |
|-------------------------------|------------|
| Branch A43 Tile | \$ 34,072 |
| Branch A45 Tile | \$ 27,561 |
| Branch A46 Tile | \$ 70,993 |
| Branch A47 Tile | \$ 17,827 |
| | |
| IMPROVEMENT - OPTION 1 | \$ 483,204 |
| IMPROVEMENT - OPTION 2 | |
| Tile Improvement Cost | \$ 483,204 |
| Storage - 1.0 AC | \$ 92,087 |
| | |
| IMPROVEMENT - OPTION 2 | \$ 575,291 |
| IMPROVEMENT - OPTION 3 | |
| Tile Improvement Cost | |
| Storage - 3.0 AC | \$ 216,128 |
| | |
| IMPROVEMENT - OPTION 3 | \$ 699,331 |

ROAD CROSSING SUMMARY

| Crossing | Road Authority | Repair Cost With Road | Repair Cost Without Road | Improvement Cost | Road Authority Cost (Difference of Repair Cost With Road and Repair Cost Without Road) | Damages Paid To Road Authority (Difference of Improvement Cost and Road Authority Cost) | | | | | | |
|--------------------------|------------------|--------------------------|-----------------------------|---------------------|---|--|--|--|--|--|--|--|
| Branch A40 Tile | | | | | | | | | | | | |
| County Road 2 | FARIBAULT COUNTY | \$ 11,545 | \$ 4,295 | \$ 31,415 | \$ 7,250 | \$ 24,165 | | | | | | |
| 310th Avenue | TOWNSHIP | \$ 6,650 | \$ 2,608 | \$ 6,650 | \$ 4,042 | \$ 2,608 | | | | | | |
| | | | | | | | | | | | | |
| TOTAL | | \$ 18,194 | \$ 6,902 | \$ 38,064 | \$ 11,292 | \$ 26,773 | | | | | | |
| | | | | | | | | | | | | |
| FARIBAULT COUNTY ROAD AU | THORITY TOTAL | \$ 11,545 | \$ 4,295 | \$ 31,415 | \$ 7,250 | \$ 24,165 | | | | | | |
| TOWNSHIP ROAD AUTHO | RITY TOTAL | \$ 6,650 | \$ 2,608 | \$ 6,650 | \$ 4,042 | \$ 2,608 | | | | | | |



ROAD CROSSINGS

BRANCH A40 TILE REPAIR COST WITH ROAD - COUNTY ROAD 2

| Item No. | Item | Unit | Quantity | Unit Price | | Amount | | |
|---------------------------------------|------------------------------------|-------------|------------|-------------|----|--------|--|--|
| 101 | MOBILIZATION | LS | 1 | \$ 400.00 | \$ | 400 | | |
| 102 | BORE 10-INCH TILE | LF | 70 | \$ 87.40 | \$ | 6,118 | | |
| 103 | INSTALL DROP INTAKE (18-INCH) | EA | 2 | \$ 988.50 | \$ | 1,977 | | |
| TOTAL | | | | | | | | |
| | | | 10% C0 | ONTINGENCY | \$ | 850 | | |
| | | | | SUBTOTAL | \$ | 9,345 | | |
| | | COUNTY A | DMINISTRA | ATION COSTS | \$ | 500 | | |
| | REPORTS, PLANS AND SPECIFICATIONS | | | | | | | |
| CONSTRUCTION STAKING & ADMINISTRATION | | | | | | | | |
| | ESTIMATED BRANCH A40 TILE REPAIR O | COST WITH I | ROAD - COL | JNTY ROAD 2 | \$ | 11,545 | | |

BRANCH A40 TILE REPAIR COST WITHOUT ROAD - COUNTY ROAD 2

| Item No. | Item | Unit | Quantity | Unit Price | | | Amount |
|---------------------------------------|--|----------|------------|------------|---------|----|--------|
| 201 | MOBILIZATION | LS | 1 | \$ | 200.00 | \$ | 200 |
| 202 | 24-INCH AGRICULTURAL TILE | LF | 70 | \$ | 32.70 | \$ | 2,289 |
| 203 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 2 | \$ | 500.00 | \$ | 1,000 |
| TOTAL | | | | | | | |
| 10% CONTINGENCY | | | | | | | |
| | | | | SU | BTOTAL | \$ | 3,838 |
| | TEMPORARY DAMAGES | AC | 0.24 | \$ | 650.00 | \$ | 157 |
| | | COUNTY A | DMINISTRA | ATION | I COSTS | \$ | 100 |
| REPORTS, PLANS AND SPECIFICATIONS | | | | | | | 100 |
| CONSTRUCTION STAKING & ADMINISTRATION | | | | | | | 100 |
| | ESTIMATED BRANCH A40 TILE REPAIR COST | | ROAD - COL | JNTY | ROAD 2 | \$ | 4,295 |

BRANCH A40 TILE IMPROVEMENT COST - COUNTY ROAD 2

| Item No. | Item | Unit | Quantity | Unit Price | | Amount | | |
|----------|---------------------------------------|------------|------------|-------------|----|--------|--|--|
| 301 | MOBILIZATION | LS | 1 | \$ 1,100.00 | \$ | 1,100 | | |
| 302 | BORE 24-INCH TILE | LF | 70 | \$ 290.00 | \$ | 20,300 | | |
| 303 | INSTALL DROP INTAKE (18-INCH) | EA | 2 | \$ 988.50 | \$ | 1,977 | | |
| TOTAL | | | | | | | | |
| | 10% CONTINGENCY | | | | | | | |
| | | | | SUBTOTAL | \$ | 25,715 | | |
| | | COUNTY A | DMINISTRA | TION COSTS | \$ | 1,300 | | |
| | REP | ORTS, PLAN | IS AND SPE | CIFICATIONS | \$ | 2,400 | | |
| | CONSTRUCTION STAKING & ADMINISTRATION | | | | | | | |
| | ESTIMATED BRANCH A40 TILE IMPR | ROVEMENT | COST - COL | JNTY ROAD 2 | \$ | 31,415 | | |



ROAD CROSSINGS

BRANCH A40 TILE REPAIR COST WITH ROAD - 310TH AVENUE

| Item No. | Item | Unit | Quantity | Unit Price | | Amount | |
|----------|--|----------|-----------|-------------|----|--------|--|
| 101 | MOBILIZATION | LS | 1 | \$ 300.00 | \$ | 300 | |
| 102 | 8-INCH AGRICULTURAL TILE | LF | 60 | \$ 14.60 | \$ | 876 | |
| 103 | OPEN CUT & RESTORE GRAVEL ROAD OR DRIVEWAY | EA | 1 | \$ 1,710.30 | \$ | 1,710 | |
| 104 | INSTALL DROP INTAKE (18-INCH) | EA | 2 | \$ 988.50 | \$ | 1,977 | |
| TOTAL | | | | | | | |
| | | | 10% C0 | ONTINGENCY | \$ | 486 | |
| | | | | SUBTOTAL | \$ | 5,350 | |
| | | COUNTY A | DMINISTRA | TION COSTS | \$ | 300 | |
| | REPORTS, PLANS AND SPECIFICATIONS | | | | | | |
| | CONSTRUCTION STAKING & ADMINISTRATION | | | | | | |
| | ESTIMATED BRANCH A40 TILE REPAIR COST WITH ROAD - 310TH AVENUE | | | | | | |

BRANCH A40 TILE REPAIR COST WITHOUT ROAD - 310TH AVENUE

| Item No. | Item | Unit | Quantity | Unit Price | | Unit Price | | | Amount |
|---------------------------------------|---|------------|-----------|------------|--------|------------|-------|--|--------|
| 201 | MOBILIZATION | LS | 1 | \$ | 100.00 | \$ | 100 | | |
| 202 | 8-INCH AGRICULTURAL TILE | LF | 60 | \$ | 14.60 | \$ | 876 | | |
| 203 | CONNECT EXISTING TILE (SIZE & MATERIAL MAY VARY) | EA | 2 | \$ | 500.00 | \$ | 1,000 | | |
| TOTAL | | | | | | | | | |
| 10% CONTINGENCY | | | | | | | | | |
| | | | | SUB | TOTAL | \$ | 2,174 | | |
| | TEMPORARY DAMAGES | AC | 0.21 | \$ | 650.00 | \$ | 134 | | |
| | | COUNTY A | DMINISTRA | ATION | COSTS | \$ | 100 | | |
| | REP | ORTS, PLAN | S AND SPE | CIFICA | ATIONS | \$ | 100 | | |
| CONSTRUCTION STAKING & ADMINISTRATION | | | | | | | 100 | | |
| | ESTIMATED BRANCH A40 TILE REPAIR COST WITHOUT ROAD - 310TH AVENUE | | | | | | | | |

BRANCH A40 TILE IMPROVEMENT COST - 310TH AVENUE

| Item No. | Item | Unit | Quantity | Unit Price | | Amount | | |
|----------|--|------------|-------------|-------------|----|--------|--|--|
| 301 | MOBILIZATION | LS | 1 | \$ 300.00 | \$ | 300 | | |
| 302 | 8-INCH AGRICULTURAL TILE | LF | 60 | \$ 14.60 | \$ | 876 | | |
| 303 | OPEN CUT & RESTORE GRAVEL ROAD OR DRIVEWAY | EA | 1 | \$ 1,710.30 | \$ | 1,710 | | |
| 304 | INSTALL DROP INTAKE (18-INCH) | EA | 2 | \$ 988.50 | \$ | 1,977 | | |
| | TOTAL | | | | | | | |
| | | | 10% C0 | ONTINGENCY | \$ | 486 | | |
| | | | | SUBTOTAL | \$ | 5,350 | | |
| | | COUNTY A | DMINISTRA | ATION COSTS | \$ | 300 | | |
| | REP | ORTS, PLAN | S AND SPE | CIFICATIONS | \$ | 500 | | |
| | CONSTRUCTION STAKING & ADMINISTRATION | | | | | | | |
| | ESTIMATED BRANCH A40 TILE IM | PROVEMEN | r COST - 31 | 0TH AVENUE | \$ | 6,650 | | |